

日立照明器具 照明特性

名称: 高天井用LEDランプ (アームタイプ)	反射率	天井	80%			70%			50%			30%			0%					
		壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%					
		床	10%												0%					
形式: BME1601MN		室指数 固有照明率 S/H=1.0																		
<備考>		0.6	0.62	0.51	0.43	0.61	0.50	0.43	0.38	0.49	0.43	0.38	0.48	0.42	0.38	0.36				
		0.8	0.72	0.62	0.55	0.71	0.61	0.54	0.49	0.60	0.54	0.49	0.58	0.53	0.49	0.47				
姿図		1	0.79	0.69	0.62	0.77	0.68	0.62	0.57	0.67	0.61	0.57	0.66	0.60	0.56	0.55				
		1.25	0.84	0.76	0.70	0.83	0.75	0.69	0.65	0.73	0.68	0.64	0.72	0.67	0.64	0.62				
光源形式		1.5	0.88	0.81	0.75	0.87	0.80	0.75	0.71	0.78	0.74	0.70	0.77	0.73	0.69	0.67				
		2	0.94	0.88	0.83	0.92	0.87	0.82	0.78	0.85	0.81	0.78	0.83	0.80	0.77	0.75				
器具光束		2.5	0.97	0.91	0.87	0.95	0.90	0.87	0.83	0.89	0.85	0.82	0.87	0.84	0.81	0.79				
		3	0.98	0.94	0.90	0.97	0.93	0.89	0.86	0.91	0.88	0.85	0.89	0.86	0.84	0.82				
16,800 lm		4	1.01	0.97	0.94	1.00	0.96	0.93	0.91	0.94	0.92	0.90	0.92	0.90	0.88	0.86				
		5	1.03	1.00	0.97	1.01	0.99	0.96	0.94	0.97	0.95	0.93	0.95	0.93	0.91	0.89				
器具効率 Ft= 100%		単体照度分布(初期値)																		
上方光束 Fu= 0%																				
下方光束 Fd= 100%																				
最大取付間隔																				
A-A 1.44 H																				
B-B H																				
保 守 率	良	0.81																		
	中	0.79																		
	否	0.75																		
光 度 (cd/1000 lm)																				
A-0		B-B	C-0	A'-0	C'-0															
0	363																			
10	375																			
20	379																			
30	364																			
40	310																			
50	224																			
60	123																			
70	49																			
80	6																			
90																				
100																				
110																				
120																				
130																				
140																				
150																				
160																				
170																				
180																				

