




日立照明器具 照明特性

名称: 高天井用LEDランプ (アームタイプ)	反射率	天井	80%			70%				50%			30%			0%
		壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%
		床	10%													
形式: BME1601MNC	室指数	固有照明率 S/H=1.0														
〈備考〉	0.6	0.61	0.49	0.42	0.59	0.49	0.42	0.37	0.48	0.41	0.37	0.47	0.41	0.37	0.35	
	0.8	0.71	0.60	0.53	0.70	0.60	0.53	0.48	0.58	0.52	0.48	0.57	0.52	0.47	0.45	
姿図 	1	0.78	0.68	0.61	0.76	0.67	0.61	0.56	0.66	0.60	0.55	0.64	0.59	0.55	0.53	
	1.25	0.83	0.75	0.68	0.82	0.74	0.68	0.63	0.72	0.67	0.63	0.71	0.66	0.62	0.60	
	1.5	0.88	0.80	0.74	0.86	0.79	0.74	0.69	0.77	0.73	0.69	0.76	0.72	0.68	0.66	
	2	0.93	0.87	0.82	0.92	0.86	0.81	0.77	0.84	0.80	0.77	0.82	0.79	0.76	0.74	
	2.5	0.96	0.91	0.86	0.95	0.90	0.86	0.82	0.88	0.84	0.81	0.86	0.83	0.80	0.78	
	3	0.98	0.93	0.90	0.97	0.92	0.89	0.86	0.90	0.87	0.84	0.88	0.86	0.83	0.81	
	4	1.01	0.97	0.94	0.99	0.96	0.93	0.90	0.94	0.91	0.89	0.92	0.90	0.88	0.85	
光源形式	5	1.02	0.99	0.97	1.01	0.98	0.96	0.94	0.96	0.94	0.92	0.94	0.92	0.91	0.88	
器具光束	7	1.04	1.02	1.01	1.03	1.01	1.00	0.98	0.99	0.98	0.96	0.97	0.96	0.95	0.92	
17,400 lm	10	1.06	1.05	1.04	1.05	1.04	1.03	1.01	1.02	1.01	1.00	0.99	0.99	0.98	0.95	
器具効率 Ft= 100%		単体照度分布 (初期値) 														
上方光束 Fu= 0%																
下方光束 Fd= 100%																
最大取付間隔																
A-A 1.44 H																
B-B H																
保守率	良	0.81	配光曲線 (cd/1000 lm) 													
	中	0.79														
	否	0.75														
光度 (cd/1000 lm)																
	A-0	B-B	C-0	A'-0	C'-0											
0	357															
10	359															
20	360															
30	346															
40	306															
50	224															
60	138															
70	58															
80	5															
90																
100																
110																
120																
130																
140																
150																
160																
170																
180																