

日立照明器具 照明特性

名称: 高天井用LEDランプ (アームタイプ)	反射率	天井	80%			70%				50%			30%			0%
		壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%
		床	10%													
形式: BME2101MNC	室指数	固有照明率 S/H=1.0														
〈備考〉		0.6	0.61	0.49	0.42	0.59	0.49	0.42	0.37	0.48	0.41	0.37	0.47	0.41	0.37	0.35
姿図		0.8	0.71	0.60	0.53	0.69	0.60	0.53	0.48	0.58	0.52	0.47	0.57	0.51	0.47	0.45
	1	0.77	0.68	0.61	0.76	0.67	0.60	0.55	0.65	0.60	0.55	0.64	0.59	0.55	0.53	
	1.25	0.83	0.75	0.68	0.82	0.74	0.68	0.63	0.72	0.67	0.62	0.71	0.66	0.62	0.60	
	1.5	0.87	0.80	0.74	0.86	0.79	0.73	0.69	0.77	0.72	0.68	0.76	0.71	0.68	0.66	
	2	0.93	0.87	0.82	0.91	0.86	0.81	0.77	0.84	0.80	0.76	0.82	0.78	0.75	0.73	
	2.5	0.96	0.91	0.86	0.94	0.89	0.85	0.82	0.88	0.84	0.81	0.86	0.83	0.80	0.78	
	3	0.98	0.93	0.89	0.96	0.92	0.88	0.85	0.90	0.87	0.84	0.88	0.85	0.83	0.81	
光源形式	4	1.00	0.97	0.93	0.99	0.96	0.93	0.90	0.93	0.91	0.89	0.91	0.89	0.87	0.85	
-	5	1.02	0.99	0.96	1.01	0.98	0.96	0.93	0.96	0.94	0.92	0.94	0.92	0.90	0.88	
器具光束	7	1.04	1.02	1.00	1.03	1.01	0.99	0.98	0.99	0.97	0.96	0.97	0.96	0.94	0.92	
22,000 lm	10	1.06	1.05	1.03	1.05	1.03	1.02	1.01	1.01	1.00	0.99	0.99	0.98	0.98	0.95	

器具効率 Ft= 100%					
上方光束 Fu= 0%					
下方光束 Fd= 100%					
最大取付間隔					
A-A		1.46 H			
B-B		H			
保守率	良	0.81			
	中	0.79			
	否	0.75			
光度 (cd/1000 lm)					
	A-0	B-B	C-0	A'-0	C'-0
0	351				
10	356				
20	360				
30	346				
40	308				
50	222				
60	133				
70	59				
80	7				
90					
100					
110					
120					
130					
140					
150					
160					
170					
180					

単体照度分布 (初期値)

単位: H

配光曲線
(cd/1000 lm)

単位: H