


日立照明器具 照明特性

形式：HD16101-EN14		天井 壁 床 室指数	80%			70%				50%			30%			0%	
			70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%	
			10%														0%
			照明率 S/H=1.0														
姿図			0.6	0.45	0.38	0.33	0.44	0.37	0.33	0.30	0.37	0.33	0.30	0.36	0.32	0.30	0.29
			0.8	0.52	0.45	0.41	0.51	0.45	0.41	0.38	0.44	0.40	0.38	0.43	0.40	0.37	0.36
			1	0.56	0.50	0.46	0.55	0.50	0.46	0.43	0.49	0.45	0.43	0.48	0.45	0.43	0.41
			1.25	0.60	0.55	0.51	0.59	0.54	0.51	0.48	0.53	0.50	0.48	0.52	0.49	0.47	0.46
			1.5	0.62	0.58	0.55	0.61	0.57	0.54	0.52	0.56	0.54	0.51	0.55	0.53	0.51	0.49
			2	0.66	0.62	0.59	0.65	0.61	0.59	0.57	0.60	0.58	0.56	0.59	0.57	0.55	0.54
			2.5	0.67	0.64	0.62	0.66	0.64	0.61	0.59	0.62	0.60	0.59	0.61	0.59	0.58	0.56
			3	0.68	0.66	0.64	0.67	0.65	0.63	0.61	0.64	0.62	0.60	0.62	0.61	0.60	0.58
光源		4	0.70	0.68	0.66	0.69	0.67	0.65	0.64	0.66	0.64	0.63	0.64	0.63	0.62	0.60	
品名	Hfコンパネ形蛍光灯ランプ	5	0.71	0.69	0.68	0.70	0.68	0.67	0.66	0.67	0.66	0.65	0.66	0.65	0.64	0.62	
形式	FHT16EX-L-A	7	0.72	0.71	0.70	0.71	0.70	0.69	0.68	0.69	0.68	0.67	0.68	0.67	0.66	0.64	
光束	1,200 lm	10	0.73	0.73	0.72	0.72	0.72	0.71	0.71	0.70	0.70	0.69	0.69	0.69	0.68	0.66	

器具効率 Ft= 68.4%
 上方光束 Fu= 0.0%
 下方光束 Fd= 68.4%

配光分類

BZ-

最大取付間隔

A-A 1.46 H

B-B H

保守率	良	0.66
	中	0.63
	否	0.55

光度 (cd/1000 lm)

	A-0	B-B	C-0
0	283		
10	302		
20	296		
30	293		
40	238		
50	138		
60	57		
70	12		
80			
90			
100			
110			
120			
130			
140			
150			
160			
170			
180			

単体照度分布(初期)

