


日立照明器具 照明特性

形式：HD24101-EN14		反 射 率	天井	80%			70%				50%			30%			0%		
			壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%		
			床	10%															0%
			室指数	照明率 S/H=1.0															
姿図 		0.6	0.44	0.38	0.34	0.44	0.37	0.34	0.31	0.37	0.33	0.31	0.36	0.33	0.31	0.30			
		0.8	0.51	0.45	0.41	0.50	0.44	0.41	0.38	0.44	0.40	0.38	0.43	0.40	0.38	0.36			
		1	0.55	0.49	0.46	0.54	0.49	0.45	0.43	0.48	0.45	0.42	0.47	0.44	0.42	0.41			
		1.25	0.58	0.53	0.50	0.57	0.53	0.50	0.47	0.52	0.49	0.47	0.51	0.48	0.46	0.45			
		1.5	0.60	0.56	0.53	0.59	0.56	0.53	0.50	0.55	0.52	0.50	0.54	0.52	0.50	0.48			
		2	0.63	0.60	0.57	0.62	0.59	0.57	0.55	0.58	0.56	0.54	0.57	0.55	0.54	0.52			
		2.5	0.65	0.62	0.60	0.64	0.61	0.59	0.57	0.60	0.58	0.57	0.59	0.57	0.56	0.55			
		3	0.66	0.63	0.61	0.65	0.63	0.61	0.59	0.61	0.60	0.58	0.60	0.59	0.58	0.56			
光源		4	0.67	0.65	0.63	0.66	0.64	0.63	0.61	0.63	0.62	0.61	0.62	0.61	0.60	0.58			
品名	Hfコンパネ形蛍光灯ランプ	5	0.68	0.66	0.65	0.67	0.66	0.64	0.63	0.64	0.63	0.62	0.63	0.62	0.61	0.60			
形式	FHT24EX-L-A	7	0.69	0.68	0.67	0.68	0.67	0.67	0.66	0.66	0.65	0.65	0.65	0.64	0.64	0.62			
光束	1,800 lm	10	0.70	0.69	0.69	0.69	0.69	0.68	0.68	0.67	0.67	0.66	0.66	0.66	0.65	0.63			

器具効率 Ft= 65.5%		
上方光束 Fu= 0.0%		
下方光束 Fd= 65.4%		
配光分類		
BZ-		
最大取付間隔		
A-A	1.26	H
B-B		H
保守率	良	0.66
	中	0.63
	否	0.55
光度 (cd/1000 lm)		
	A-0	B-B
0	327	
10	343	
20	317	
30	283	
40	212	
50	122	
60	48	
70	10	
80	1	
90	1	
100		
110		
120		
130		
140		
150		
160		
170		
180		

単体照度分布(初期)

