


日立照明器具 照明特性

形式：HD4201-EX200		反 射 率	天井	80%			70%				50%			30%			0%
<連続調光形>			壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%
			床	10%													
			室指数	照明率 S/H=1.0													
姿図 		0.6	0.33	0.25	0.20	0.32	0.24	0.19	0.16	0.24	0.19	0.16	0.23	0.19	0.16	0.15	
		0.8	0.39	0.31	0.26	0.38	0.31	0.26	0.22	0.30	0.26	0.22	0.29	0.25	0.22	0.21	
		1	0.43	0.36	0.31	0.42	0.36	0.31	0.27	0.35	0.30	0.27	0.34	0.30	0.27	0.25	
		1.25	0.47	0.41	0.36	0.46	0.40	0.35	0.32	0.39	0.35	0.32	0.38	0.34	0.31	0.30	
		1.5	0.50	0.44	0.40	0.49	0.44	0.39	0.36	0.42	0.39	0.36	0.41	0.38	0.35	0.34	
		2	0.54	0.49	0.45	0.53	0.48	0.45	0.42	0.47	0.44	0.41	0.46	0.43	0.41	0.39	
		2.5	0.56	0.52	0.48	0.55	0.51	0.48	0.45	0.50	0.47	0.45	0.49	0.46	0.44	0.42	
		3	0.58	0.54	0.51	0.57	0.53	0.50	0.48	0.52	0.49	0.47	0.51	0.48	0.46	0.45	
光源		4	0.60	0.57	0.54	0.59	0.56	0.54	0.51	0.55	0.53	0.51	0.53	0.52	0.50	0.48	
品名	Hfコンパネ形蛍光灯ランプ	5	0.61	0.59	0.56	0.60	0.58	0.56	0.54	0.57	0.55	0.53	0.55	0.54	0.52	0.51	
形式	FHT42EX-N-A	7	0.63	0.61	0.59	0.62	0.60	0.59	0.57	0.59	0.58	0.56	0.57	0.56	0.55	0.54	
光束	6,400 lm	10	0.64	0.63	0.62	0.63	0.62	0.61	0.60	0.61	0.60	0.59	0.59	0.59	0.58	0.56	

器具効率 Ft= 61.1%
 上方光束 Fu= 0.1%
 下方光束 Fd= 61.0%


配光分類
BZ-

最大取付間隔
 A-A 2.08 H
 B-B H

保守率	良	0.66
	中	0.63
	否	0.55

光度 (cd/1000 lm)			
	A-0	B-B	C-0
0	105		
10	119		
20	141		
30	158		
40	164		
50	149		
60	111		
70	67		
80	28		
90	2		
100			
110			
120			
130			
140			
150			
160			
170			
180			

単体照度分布(初期)



配光曲線

