


日立照明器具 照明特性

形式： HPF4301A-EN(32W)		反 射 率	80%			70%				50%			30%			0%		
			壁 床	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%	
				10%														0%
				照明率 S/H=1.0														
室指数																		
	姿図	0.6	0.46	0.36	0.29	0.44	0.35	0.29	0.25	0.33	0.28	0.24	0.32	0.27	0.23	0.21		
		0.8	0.54	0.45	0.38	0.52	0.44	0.38	0.33	0.42	0.36	0.33	0.40	0.35	0.32	0.29		
		1	0.59	0.51	0.45	0.58	0.50	0.44	0.39	0.47	0.42	0.38	0.45	0.41	0.37	0.35		
		1.25	0.64	0.56	0.50	0.62	0.55	0.50	0.45	0.52	0.48	0.44	0.50	0.46	0.43	0.40		
		1.5	0.68	0.61	0.55	0.66	0.59	0.54	0.50	0.56	0.52	0.48	0.54	0.50	0.47	0.43		
		2	0.72	0.66	0.61	0.70	0.64	0.60	0.56	0.61	0.58	0.54	0.58	0.55	0.52	0.49		
		2.5	0.75	0.69	0.65	0.72	0.68	0.64	0.60	0.64	0.61	0.58	0.61	0.58	0.56	0.52		
		3	0.76	0.72	0.68	0.74	0.70	0.66	0.63	0.66	0.63	0.61	0.63	0.61	0.58	0.54		
光源		4	0.79	0.75	0.71	0.76	0.73	0.70	0.67	0.69	0.67	0.64	0.66	0.64	0.62	0.58		
品名	Hfコンパ外形蛍光ランプ	5	0.80	0.77	0.74	0.78	0.75	0.72	0.70	0.72	0.69	0.67	0.68	0.66	0.65	0.60		
形式	FHT32EX-N-A	7	0.82	0.80	0.78	0.80	0.78	0.76	0.74	0.74	0.73	0.71	0.71	0.70	0.68	0.64		
光束	7,200 lm	10	0.84	0.82	0.81	0.82	0.81	0.79	0.78	0.77	0.76	0.75	0.73	0.72	0.71	0.67		

器具効率 Ft= 82.2%
 上方光束 Fu= 9.3%
 下方光束 Fd= 73.0%

配光分類
BZ-

最大取付間隔
 A-A 2.10 H
 B-B H

保守率	良	0.66
	中	0.63
	否	0.55

光度 (cd/1000 lm)			
	A-0	B-B	C-0
0	135		
10	152		
20	200		
30	254		
40	252		
50	169		
60	58		
70	42		
80	41		
90	39		
100	31		
110	21		
120	9		
130	4		
140	3		
150	3		
160	2		
170	3		
180			

単体照度分布(初期)

