

日立照明器具 照明特性

形式： HPF4302A-EN(32W)			反 射 率	天井	80%			70%				50%			30%			0%			
				壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%			
				床	10%																0%
				室指数	照明率 S/H=1.0																
姿図 			0.6	0.46	0.38	0.33	0.44	0.37	0.32	0.29	0.36	0.31	0.28	0.34	0.31	0.28	0.26				
			0.8	0.53	0.46	0.41	0.52	0.45	0.41	0.37	0.44	0.40	0.36	0.42	0.39	0.36	0.34				
			1	0.58	0.52	0.47	0.57	0.51	0.46	0.43	0.49	0.45	0.42	0.47	0.44	0.41	0.39				
			1.25	0.62	0.56	0.52	0.61	0.55	0.51	0.48	0.53	0.50	0.47	0.51	0.48	0.46	0.44				
			1.5	0.65	0.60	0.56	0.64	0.59	0.55	0.52	0.57	0.54	0.51	0.55	0.52	0.50	0.47				
			2	0.69	0.65	0.61	0.67	0.63	0.60	0.58	0.61	0.58	0.56	0.59	0.57	0.55	0.52				
			2.5	0.71	0.67	0.64	0.69	0.66	0.63	0.61	0.63	0.61	0.59	0.61	0.59	0.57	0.55				
			3	0.72	0.69	0.66	0.70	0.68	0.65	0.63	0.65	0.63	0.61	0.62	0.61	0.59	0.56				
光源			4	0.74	0.71	0.69	0.72	0.70	0.68	0.66	0.67	0.65	0.64	0.64	0.63	0.62	0.59				
品名	Hコンパクト形蛍光ランプ		5	0.75	0.73	0.71	0.73	0.71	0.70	0.68	0.69	0.67	0.66	0.66	0.65	0.64	0.60				
形式	FHT32EX-N-A		7	0.76	0.75	0.74	0.75	0.73	0.72	0.71	0.71	0.70	0.69	0.68	0.67	0.66	0.63				
光束	7,200 lm		10	0.77	0.77	0.76	0.76	0.75	0.74	0.74	0.72	0.72	0.71	0.69	0.69	0.69	0.65				

器具効率 Ft= 74.1%			
上方光束 Fu= 6.9%			
下方光束 Fd= 67.2%			
配光分類			
BZ-			
最大取付間隔			
A-A 1.60		H	
B-B		H	
保守率	良	0.66	
	中	0.63	
	否	0.55	
光 度 (cd/1000 lm)			
	A-0	B-B	C-0
0	233		
10	255		
20	277		
30	259		
40	237		
50	166		
60	53		
70	11		
80	4		
90	3		
100	5		
110	7		
120	12		
130	17		
140	19		
150	18		
160	10		
170	7		
180			

単体照度分布(初期)

