

日立照明器具 照明特性

形式： HPF4302A-EN(42W)			反 射 率	天井	80%			70%				50%			30%			0%			
				壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%			
				床	10%																0%
				室指数	照明率 S/H=1.0																
姿図 			0.6	0.45	0.36	0.31	0.44	0.36	0.30	0.27	0.34	0.30	0.26	0.33	0.29	0.26	0.24				
			0.8	0.53	0.45	0.39	0.52	0.44	0.39	0.35	0.43	0.38	0.34	0.41	0.37	0.34	0.32				
			1	0.58	0.51	0.46	0.57	0.50	0.45	0.41	0.48	0.44	0.40	0.46	0.43	0.40	0.37				
			1.25	0.63	0.56	0.51	0.61	0.55	0.51	0.47	0.53	0.49	0.46	0.51	0.48	0.45	0.43				
			1.5	0.66	0.60	0.56	0.65	0.59	0.55	0.52	0.57	0.53	0.51	0.55	0.52	0.49	0.47				
			2	0.70	0.66	0.62	0.69	0.64	0.61	0.58	0.62	0.59	0.56	0.60	0.57	0.55	0.52				
			2.5	0.73	0.69	0.65	0.71	0.67	0.64	0.62	0.65	0.62	0.60	0.63	0.60	0.58	0.55				
			3	0.74	0.71	0.68	0.73	0.69	0.67	0.64	0.67	0.64	0.62	0.64	0.62	0.61	0.58				
光源			4	0.76	0.73	0.71	0.75	0.72	0.70	0.68	0.69	0.68	0.66	0.67	0.65	0.64	0.61				
品名	Hfコンパクト形蛍光灯ランプ		5	0.78	0.75	0.73	0.76	0.74	0.72	0.70	0.71	0.70	0.68	0.69	0.67	0.66	0.63				
形式	FHT42EX-N-A		7	0.79	0.78	0.76	0.78	0.76	0.75	0.74	0.73	0.72	0.71	0.71	0.70	0.69	0.66				
光束	9,600 lm		10	0.80	0.79	0.78	0.79	0.78	0.77	0.76	0.75	0.74	0.74	0.73	0.72	0.71	0.68				

器具効率 Ft= 77.0%
 上方光束 Fu= 5.9%
 下方光束 Fd= 71.2%


配光分類
BZ-

最大取付間隔
 A-A 1.56 H
 B-B H

保守率	良	0.66
	中	0.63
	否	0.55

光度 (cd/1000 lm)			
	A-0	B-B	C-0
0	221		
10	250		
20	251		
30	226		
40	219		
50	184		
60	106		
70	26		
80	5		
90	2		
100	4		
110	6		
120	10		
130	14		
140	17		
150	16		
160	10		
170	6		
180			

単体照度分布(初期)



配光曲線

