


日立照明器具 照明特性

形式： HTM4170A-EU14+HBC4173		反 射 率	天井	80%			70%				50%			30%			0%
<高出力形>			壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%
			床	10%													
			室指数	照明率 S/H=1.0													
		0.6	0.36	0.30	0.26	0.35	0.29	0.26	0.23	0.29	0.25	0.23	0.28	0.25	0.23	0.22	
		0.8	0.42	0.37	0.33	0.41	0.36	0.33	0.30	0.36	0.33	0.30	0.35	0.32	0.30	0.29	
		1	0.46	0.41	0.38	0.45	0.41	0.38	0.35	0.40	0.37	0.35	0.39	0.37	0.35	0.34	
		1.25	0.49	0.45	0.42	0.48	0.45	0.42	0.39	0.44	0.41	0.39	0.43	0.41	0.39	0.38	
		1.5	0.51	0.48	0.45	0.51	0.47	0.45	0.43	0.46	0.44	0.42	0.46	0.44	0.42	0.41	
		2	0.54	0.51	0.49	0.53	0.51	0.49	0.47	0.50	0.48	0.46	0.49	0.47	0.46	0.45	
		2.5	0.55	0.53	0.51	0.55	0.52	0.51	0.49	0.51	0.50	0.48	0.50	0.49	0.48	0.47	
		3	0.56	0.54	0.52	0.56	0.54	0.52	0.50	0.53	0.51	0.50	0.52	0.50	0.49	0.48	
光 源		4	0.57	0.56	0.54	0.57	0.55	0.54	0.53	0.54	0.53	0.52	0.53	0.52	0.51	0.50	
品名	Hf蛍光ランプ ^o	5	0.58	0.57	0.56	0.58	0.56	0.55	0.54	0.55	0.54	0.53	0.54	0.53	0.53	0.51	
形式	FHF32EX-N-H	7	0.59	0.59	0.58	0.59	0.58	0.57	0.57	0.57	0.56	0.56	0.56	0.55	0.55	0.53	
光束	4.950 lm	10	0.60	0.60	0.59	0.60	0.59	0.59	0.58	0.58	0.58	0.57	0.57	0.57	0.56	0.55	

器具効率 Ft= 56.3%			
上方光束 Fu= 0.0%			
下方光束 Fd= 56.3%			
配光分類			
BZ-			
最大取付間隔			
A-A		1.92	H
B-B		1.24	H
保守率	良	0.74	
	中	0.70	
	否	0.62	
光度 (cd/1000 lm)			
	A-0	B-B	C-0
0	191	191	191
10	206	185	197
20	248	175	214
30	319	156	241
40	320	132	260
50	148	94	164
60	23	4	27
70	1	1	1
80			
90			
100			
110			
120			
130			
140			
150			
160			
170			
180			

单体照度分布(初期)



配光曲線

