

日立照明器具 照明特性

形式：LDE1011WL		反 射 率	天井	80%			70%				50%			30%			0%		
<高演色タイプ> <電球色(2800k,Ra92)>			壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%		
			床	10%															0%
			室指数	照明率 S/H=1.0															
		0.6	0.70	0.60	0.54	0.69	0.60	0.54	0.50	0.59	0.54	0.50	0.58	0.54	0.50	0.48			
		0.8	0.79	0.70	0.65	0.78	0.70	0.64	0.60	0.69	0.64	0.60	0.68	0.63	0.60	0.58			
		1	0.84	0.77	0.71	0.83	0.76	0.71	0.67	0.75	0.70	0.67	0.74	0.70	0.66	0.65			
		1.25	0.89	0.82	0.77	0.88	0.82	0.77	0.73	0.80	0.76	0.73	0.79	0.75	0.72	0.70			
		1.5	0.93	0.87	0.82	0.91	0.86	0.81	0.78	0.84	0.80	0.77	0.83	0.79	0.77	0.75			
		2	0.97	0.92	0.88	0.95	0.91	0.87	0.84	0.89	0.86	0.83	0.88	0.85	0.83	0.81			
		2.5	0.99	0.95	0.91	0.98	0.94	0.91	0.88	0.92	0.89	0.87	0.90	0.88	0.86	0.84			
		3	1.00	0.97	0.94	0.99	0.96	0.93	0.90	0.94	0.91	0.89	0.92	0.90	0.88	0.86			
光 源		4	1.02	0.99	0.97	1.01	0.98	0.96	0.94	0.96	0.94	0.93	0.95	0.93	0.91	0.89			
品名	LED6.7W	5	1.04	1.01	0.99	1.02	1.00	0.98	0.97	0.98	0.97	0.95	0.96	0.95	0.94	0.91			
形式		7	1.06	1.04	1.02	1.04	1.03	1.02	1.00	1.01	1.00	0.99	0.99	0.98	0.97	0.94			
光束	320 lm	10	1.07	1.06	1.05	1.06	1.05	1.04	1.03	1.03	1.02	1.01	1.01	1.00	1.00	0.97			

器具効率 Ft= 100.0%

上方光束 Fu= 0.0%

下方光束 Fd= 100.0%

配光分類

BZ-

最大取付間隔

A-A 1.28 H


B-B H

保守率	良	0.71
	中	0.68
	否	0.64

光度 (cd/1000 lm)

	A-0	B-B	C-0
0	513		
10	518		
20	561		
30	477		
40	288		
50	143		
60	59		
70	30		
80	11		
90			
100			
110			
120			
130			
140			
150			
160			
170			
180			

単体照度分布(初期)



配光曲線

