




日立照明器具 照明特性

名称: LEDダウンライト	反射率	天井	80%				70%				50%			30%			0%		
		壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%			
		床	10%														0%		
形式: LDE3204WN	室指数	固有照明率 S/H=1.0																	
＜備考＞	0.6	0.64	0.53	0.46	0.62	0.52	0.46	0.41	0.51	0.45	0.41	0.50	0.45	0.41	0.39				
	0.8	0.74	0.64	0.58	0.73	0.63	0.57	0.53	0.62	0.57	0.52	0.61	0.56	0.52	0.50				
姿図 	1	0.80	0.72	0.65	0.79	0.71	0.65	0.60	0.69	0.64	0.60	0.68	0.63	0.60	0.58				
	1.25	0.86	0.78	0.72	0.84	0.77	0.72	0.68	0.76	0.71	0.67	0.74	0.70	0.67	0.65				
	1.5	0.90	0.83	0.78	0.88	0.82	0.77	0.73	0.81	0.76	0.73	0.79	0.75	0.72	0.70				
	2	0.95	0.89	0.85	0.93	0.88	0.84	0.81	0.87	0.83	0.80	0.85	0.82	0.79	0.77				
	2.5	0.97	0.93	0.89	0.96	0.92	0.88	0.85	0.90	0.87	0.84	0.88	0.85	0.83	0.81				
	3	0.99	0.95	0.91	0.98	0.94	0.91	0.88	0.92	0.89	0.87	0.90	0.88	0.86	0.83				
光源形式 -	4	1.01	0.98	0.95	1.00	0.97	0.94	0.92	0.95	0.93	0.91	0.93	0.91	0.89	0.87				
	5	1.03	1.00	0.98	1.02	0.99	0.97	0.95	0.97	0.95	0.94	0.95	0.94	0.92	0.90				
器具光束 1,670 lm	7	1.05	1.03	1.01	1.04	1.02	1.00	0.99	1.00	0.99	0.97	0.98	0.97	0.96	0.93				
	10	1.06	1.05	1.04	1.05	1.04	1.03	1.02	1.02	1.01	1.00	1.00	0.99	0.99	0.96				
器具効率 Ft= 100%		単体照度分布(初期値)  2.0 1.0 0.0 1.0 2.0 0.0 1.0 2.0 水平距離(m) 0-200 200-400 400-600 600-800 800-1000																	
上方光束 Fu= 0%																			
下方光束 Fd= 100%																			
最大取付間隔																			
A-A 1.30 H																			
B-B H																			
保守率	良	0.79																	
	中	0.75																	
	否	0.67																	
光度 (cd/1000 lm)		配光曲線 (cd/1000 lm)  180 150 120 90 60 30 0 450.0 400.0 350.0 300.0 250.0 200.0 150.0 100.0 50.0 0.0 A B C-C'																	
	A-0															B-B	C-0	A'-0	C'-0
0	431																		
10	427																		
20	412																		
30	378																		
40	321																		
50	235																		
60	100																		
70	21																		
80	6																		
90	0																		
100																			
110																			
120																			
130																			
140																			
150																			
160																			
170																			
180																			