

日立照明器具 照明特性

形式: LDE3301WL		天井	80%			70%				50%			30%			0%
<高演色タイプ> <電球色(3000K,Ra92)> <埋込穴Φ150>	反射率	壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%
		床	10%													0%
		室指数	照明率 S/H=1.0													
姿図 	0.6		0.65	0.55	0.48	0.64	0.54	0.48	0.44	0.54	0.48	0.44	0.53	0.47	0.43	0.42
	0.8		0.75	0.66	0.59	0.74	0.65	0.59	0.55	0.64	0.59	0.54	0.63	0.58	0.54	0.52
	1		0.81	0.73	0.67	0.80	0.72	0.67	0.62	0.71	0.66	0.62	0.70	0.65	0.61	0.60
	1.25		0.87	0.79	0.74	0.85	0.78	0.73	0.69	0.77	0.72	0.69	0.76	0.71	0.68	0.66
	1.5		0.91	0.84	0.79	0.89	0.83	0.78	0.75	0.82	0.77	0.74	0.80	0.76	0.73	0.71
	2		0.95	0.90	0.86	0.94	0.89	0.85	0.82	0.87	0.84	0.81	0.86	0.83	0.80	0.78
	2.5		0.98	0.93	0.90	0.96	0.92	0.89	0.86	0.91	0.88	0.85	0.89	0.86	0.84	0.82
	3		0.99	0.96	0.92	0.98	0.95	0.91	0.89	0.93	0.90	0.88	0.91	0.89	0.86	0.84
	4		1.02	0.99	0.96	1.00	0.97	0.95	0.93	0.95	0.93	0.91	0.94	0.92	0.90	0.88
	5		1.03	1.01	0.98	1.02	1.00	0.98	0.96	0.98	0.96	0.94	0.96	0.94	0.93	0.90
光源																
品名	LED17.5W															
形式																
光束	840 lm															
		10	1.07	1.06	1.05	1.05	1.04	1.04	1.03	1.02	1.02	1.01	1.00	1.00	0.99	0.96

器具効率 Ft= 100.0%
 上方光束 Fu= 0.0%
 下方光束 Fd= 100.0%

配光分類

BZ-

最大取付間隔

A-A 1.24 H


B-B H

保守率	良	0.71
	中	0.68
	否	0.64

光度 (cd/1000 lm)

	A-0	B-B	C-0
0	485		
10	473		
20	445		
30	400		
40	318		
50	199		
60	96		
70	28		
80	2		
90			
100			
110			
120			
130			
140			
150			
160			
170			
180			

単体照度分布(初期)



配光曲線

