




日立照明器具 照明特性

名称: LEDダウンライト	反射率	天井	80%				70%				50%			30%			0%
		壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%	
		床	10%														0%
形式: LDE34AMD-JX14A	室指数	固有照明率 S/H=1.0															
＜備考＞	0.6	0.68	0.58	0.52	0.67	0.57	0.51	0.47	0.56	0.51	0.47	0.56	0.51	0.47	0.45		
	0.8	0.77	0.68	0.62	0.76	0.68	0.62	0.58	0.67	0.62	0.58	0.66	0.61	0.57	0.56		
姿図 	1	0.83	0.75	0.70	0.82	0.75	0.69	0.65	0.73	0.68	0.65	0.72	0.68	0.64	0.63		
	1.25	0.88	0.81	0.76	0.87	0.81	0.76	0.72	0.79	0.75	0.71	0.78	0.74	0.71	0.69		
	1.5	0.92	0.86	0.81	0.91	0.85	0.80	0.77	0.83	0.79	0.76	0.82	0.78	0.76	0.74		
	2	0.96	0.91	0.87	0.95	0.91	0.87	0.84	0.89	0.86	0.83	0.87	0.84	0.82	0.80		
	2.5	0.99	0.95	0.91	0.97	0.94	0.90	0.87	0.92	0.89	0.86	0.90	0.88	0.85	0.83		
	3	1.00	0.97	0.93	0.99	0.96	0.93	0.90	0.94	0.91	0.89	0.92	0.90	0.88	0.86		
光源形式 -	4	1.02	0.99	0.97	1.01	0.98	0.96	0.94	0.96	0.94	0.92	0.94	0.93	0.91	0.89		
	5	1.04	1.01	0.99	1.03	1.00	0.98	0.97	0.98	0.97	0.95	0.96	0.95	0.94	0.91		
器具光束 3,700 lm	7	1.06	1.04	1.03	1.04	1.03	1.02	1.00	1.01	1.00	0.99	0.99	0.98	0.97	0.94		
	10	1.07	1.06	1.05	1.06	1.05	1.04	1.03	1.03	1.02	1.02	1.01	1.00	1.00	0.97		
器具効率 Ft= 100%		単体照度分布(初期値) 															
上方光束 Fu= 0%																	
下方光束 Fd= 100%																	
最大取付間隔																	
A-A 1.26 H																	
B-B H																	
保守率	良	0.79															
	中	0.75															
	否	0.67															
光度 (cd/1000 lm)																	
	A-0	B-B	C-0	A'-0	C'-0												
0	509																
10	510																
20	491																
30	441																
40	325																
50	169																
60	71																
70	26																
80	4																
90																	
100																	
110																	
120																	
130																	
140																	
150																	
160																	
170																	
180																	

配光曲線
(cd/1000 lm)



A
B
C-C'

