

日立照明器具 照明特性

形式: LDE4303WN <昼白色(5,000K,Ra75)> <埋込穴φ150>		天井	80%			70%				50%			30%			0%
反射率		壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%
		床	10%													
室指数		照明率 S/H=1.0														
		0.6	0.65	0.55	0.48	0.64	0.54	0.48	0.44	0.53	0.48	0.43	0.53	0.47	0.43	0.42
		0.8	0.75	0.66	0.60	0.74	0.65	0.59	0.55	0.64	0.59	0.55	0.63	0.58	0.54	0.53
		1	0.82	0.73	0.67	0.80	0.73	0.67	0.63	0.71	0.66	0.62	0.70	0.65	0.62	0.60
		1.25	0.87	0.80	0.74	0.86	0.79	0.74	0.70	0.77	0.73	0.69	0.76	0.72	0.69	0.67
		1.5	0.91	0.84	0.79	0.90	0.84	0.79	0.75	0.82	0.78	0.74	0.80	0.77	0.74	0.72
		2	0.96	0.90	0.86	0.94	0.89	0.85	0.82	0.88	0.84	0.81	0.86	0.83	0.81	0.78
		2.5	0.98	0.94	0.90	0.97	0.93	0.89	0.86	0.91	0.88	0.85	0.89	0.87	0.84	0.82
		3	1.00	0.96	0.92	0.98	0.95	0.92	0.89	0.93	0.90	0.88	0.91	0.89	0.87	0.84
光源		4	1.02	0.99	0.96	1.01	0.98	0.95	0.93	0.96	0.94	0.92	0.94	0.92	0.90	0.88
品名	LED19.5W	5	1.03	1.01	0.99	1.02	1.00	0.98	0.96	0.98	0.96	0.94	0.96	0.94	0.93	0.90
形式		7	1.05	1.04	1.02	1.04	1.02	1.01	1.00	1.00	0.99	0.98	0.98	0.97	0.96	0.94
光束	1,930 lm	10	1.07	1.06	1.05	1.06	1.05	1.04	1.03	1.03	1.02	1.01	1.00	1.00	0.99	0.97

器具効率 Ft= 100.0%		单体照度分布(初期) 800 600 400 200 0.0 1.0 2.0 2.0 1.0 0.0 1.0 2.0 A ← 水平距離(m) → B 0-200 200-400 400-600 600-800 800-1000 高さ(m)														
上方光束 Fu= 0.0%																
下方光束 Fd= 100.0%																
最大取付間隔																
A-A 1.26 H																
B-B H																
保守率	光源寿命 (h)	40,000	60,000													
		良	0.77	0.71												
	中	0.73	0.67													
	否	0.64	0.59													
光度 (cd/1000 lm)																
	A-0	B-B	C-0	A'-0	C'-0											
0	467															
10	464															
20	445															
30	397															
40	320															
50	222															
60	92															
70	12															
80	6															
90																
100																
110																
120																
130																
140																
150																
160																
170																
180																

配光曲線	
180	500.0
150	450.0
120	400.0
90	350.0
60	300.0
30	250.0
0	200.0
30	150.0
60	100.0
90	50.0
120	0.0
150	50.0
180	100.0
150	150.0
120	200.0
90	250.0
60	300.0
30	350.0
0	400.0
30	450.0
60	500.0
90	500.0
120	500.0
150	500.0
180	500.0
— A - - - B - - - C-C'	

配光曲線

