




日立照明器具 照明特性

名称: LEDダウンライト		反射率	天井	80%			70%			50%			30%			0%			
				壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%	
形式: LDE74ANL-JX14A		室指数	床	10%													0%		
				固有照明率 S/H=1.0															
＜備考＞		0.6	0.73	0.65	0.59	0.72	0.64	0.59	0.55	0.63	0.59	0.55	0.63	0.58	0.55	0.54			
		0.8	0.82	0.74	0.69	0.81	0.74	0.69	0.65	0.73	0.68	0.65	0.72	0.68	0.65	0.63			
姿図 		1	0.87	0.80	0.75	0.86	0.80	0.75	0.72	0.79	0.74	0.71	0.77	0.74	0.71	0.69			
		1.25	0.91	0.86	0.81	0.90	0.85	0.81	0.77	0.83	0.80	0.77	0.82	0.79	0.76	0.75			
		1.5	0.95	0.89	0.85	0.93	0.89	0.85	0.82	0.87	0.84	0.81	0.86	0.83	0.81	0.79			
		2	0.98	0.94	0.91	0.97	0.93	0.90	0.88	0.92	0.89	0.87	0.90	0.88	0.86	0.84			
		2.5	1.00	0.97	0.94	0.99	0.96	0.93	0.91	0.94	0.92	0.90	0.93	0.91	0.89	0.87			
		3	1.02	0.98	0.96	1.00	0.98	0.95	0.93	0.96	0.94	0.92	0.94	0.92	0.91	0.88			
光源形式		4	1.03	1.01	0.99	1.02	1.00	0.98	0.96	0.98	0.96	0.95	0.96	0.95	0.93	0.91			
		5	1.04	1.02	1.01	1.03	1.01	1.00	0.98	0.99	0.98	0.97	0.98	0.96	0.95	0.93			
器具光束 6,400 lm		7	1.06	1.05	1.03	1.05	1.04	1.03	1.01	1.02	1.01	1.00	1.00	0.99	0.98	0.96			
		10	1.07	1.07	1.06	1.06	1.05	1.05	1.04	1.03	1.03	1.02	1.01	1.01	1.00	0.98			
器具効率 Ft= 100%		単体照度分布(初期値) 																	
上方光束 Fu= 0%																			
下方光束 Fd= 100%																			
最大取付間隔																			
A-A 0.94 H																			
B-B H																			
保守率	良															0.79			
	中															0.75			
	否															0.97			
光度 (cd/1000 lm)		配光曲線 (cd/1000 lm) 																	
	A-0															B-B	C-0	A'-0	C'-0
0	793																		
10	732																		
20	601																		
30	449																		
40	292																		
50	136																		
60	49																		
70	7																		
80																			
90																			
100																			
110																			
120																			
130																			
140																			
150																			
160																			
170																			
180																			