




日立照明器具 照明特性

名称: LEDダウンライト	反射率	天井	80%				70%				50%			30%			0%		
		壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%			
		床	10%														0%		
形式: LDE94AMN-JX14A	室指数	固有照明率 S/H=1.0																	
＜備考＞	0.6	0.68	0.58	0.52	0.67	0.58	0.52	0.48	0.57	0.51	0.47	0.56	0.51	0.47	0.46				
	0.8	0.77	0.69	0.63	0.76	0.68	0.62	0.58	0.67	0.62	0.58	0.66	0.61	0.58	0.56				
姿図 	1	0.83	0.75	0.70	0.82	0.75	0.69	0.65	0.73	0.69	0.65	0.72	0.68	0.65	0.63				
	1.25	0.88	0.81	0.76	0.87	0.80	0.76	0.72	0.79	0.75	0.71	0.78	0.74	0.71	0.69				
	1.5	0.92	0.86	0.81	0.91	0.85	0.80	0.77	0.83	0.79	0.76	0.82	0.78	0.76	0.74				
	2	0.96	0.91	0.87	0.95	0.90	0.87	0.83	0.89	0.85	0.83	0.87	0.84	0.82	0.80				
	2.5	0.99	0.94	0.91	0.97	0.93	0.90	0.87	0.92	0.89	0.86	0.90	0.87	0.85	0.83				
	3	1.00	0.96	0.93	0.99	0.95	0.92	0.90	0.93	0.91	0.89	0.92	0.90	0.88	0.85				
光源形式 -	4	1.02	0.99	0.97	1.01	0.98	0.96	0.94	0.96	0.94	0.92	0.94	0.93	0.91	0.89				
	5	1.04	1.01	0.99	1.02	1.00	0.98	0.96	0.98	0.96	0.95	0.96	0.95	0.93	0.91				
器具光束 9,500 lm	7	1.05	1.04	1.02	1.04	1.03	1.01	1.00	1.01	0.99	0.98	0.99	0.98	0.97	0.94				
	10	1.07	1.06	1.05	1.06	1.05	1.04	1.03	1.03	1.02	1.01	1.01	1.00	0.99	0.97				
器具効率 Ft= 100%		単体照度分布(初期値) 																	
上方光束 Fu= 0%																			
下方光束 Fd= 100%																			
最大取付間隔																			
A-A 1.26 H																			
B-B H																			
保守率	良	0.79																	
	中	0.75																	
	否	0.67																	
光度 (cd/1000 lm)		配光曲線 (cd/1000 lm) 																	
	A-0															B-B	C-0	A'-0	C'-0
0	514																		
10	516																		
20	505																		
30	440																		
40	315																		
50	164																		
60	72																		
70	27																		
80	5																		
90																			
100																			
110																			
120																			
130																			
140																			
150																			
160																			
170																			
180																			