

日立照明器具 照明特性

名称:直管形LEDランプ	天井	80%			70%				50%			30%			0%		
		壁	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%		
形式:LDK110SS・N/54/69E	床	10%															0%
		照明率 S/H=1.0															
<備考>FLR110形 定格出力タイプ	0.6	0.52	0.40	0.32	0.50	0.39	0.31	0.26	0.36	0.30	0.25	0.34	0.28	0.24	0.21		
	0.8	0.61	0.49	0.41	0.59	0.48	0.40	0.34	0.45	0.38	0.33	0.42	0.36	0.31	0.28		
	1	0.67	0.56	0.48	0.65	0.54	0.46	0.40	0.50	0.44	0.39	0.47	0.41	0.37	0.33		
	1.25	0.73	0.62	0.54	0.70	0.60	0.53	0.47	0.56	0.50	0.45	0.53	0.47	0.43	0.38		
	1.5	0.77	0.68	0.60	0.74	0.65	0.58	0.52	0.61	0.55	0.50	0.57	0.52	0.48	0.43		
	2	0.83	0.75	0.68	0.80	0.72	0.66	0.60	0.67	0.62	0.57	0.63	0.58	0.55	0.49		
	2.5	0.87	0.79	0.73	0.83	0.77	0.71	0.66	0.72	0.67	0.62	0.67	0.63	0.59	0.53		
姿図	3	0.89	0.82	0.77	0.86	0.80	0.74	0.70	0.75	0.70	0.66	0.70	0.66	0.63	0.56		
	4	0.92	0.87	0.82	0.89	0.84	0.80	0.76	0.79	0.75	0.72	0.74	0.71	0.68	0.61		
	5	0.95	0.90	0.86	0.91	0.87	0.83	0.80	0.82	0.78	0.75	0.76	0.74	0.71	0.65		
	7	0.97	0.94	0.91	0.94	0.91	0.88	0.85	0.85	0.83	0.81	0.80	0.78	0.76	0.69		
	10	1.00	0.97	0.95	0.96	0.94	0.92	0.90	0.88	0.87	0.85	0.83	0.82	0.80	0.73		
	器具効率 Ft=																
	上方光束 Fu=																
下方光束 Fd=																	
最大取付間隔																	
A-A		H															
B-B		H															
保守率	良																
	中否																
光度 (cd/1000 lm)																	
	A-0	B-B	C-0	A'-0	C'-0												
0	228	228	228														
10	225	223	224														
20	217	212	215														
30	205	195	200														
40	189	170	180														
50	170	138	157														
60	150	103	130														
70	130	63	105														
80	109	31	80														
90	91	3	60														
100	74	2	46														
110	57	3	34														
120	44	4	25														
130	32	6	19														
140	23	6	15														
150	16	7	12														
160	12	8	10														
170	9	8	9														
180	8	8	8														

単位照度分布 (初期値)

高さ(m)

水平距離(m)

A← →B

配光曲線 (cd/1000 lm)

A

B

C-C'