

## 日立照明器具 照明特性

名称: 直管形LEDランプ	反射率	天井	80%			70%			50%			30%			0%	
		壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%
		床	10%												0%	
形式: LDK20SS-N/10/13NA	室指数	照明率 S/H=1.0														
<備考> FL20形 定格出力(H) タイプ (昼白色)	0.6	0.52	0.39	0.31	0.49	0.38	0.30	0.25	0.35	0.29	0.24	0.32	0.27	0.23	0.19	
	0.8	0.60	0.48	0.40	0.58	0.46	0.39	0.33	0.43	0.36	0.31	0.40	0.34	0.30	0.25	
姿図	1	0.66	0.55	0.47	0.63	0.53	0.45	0.39	0.49	0.42	0.37	0.45	0.39	0.35	0.30	
B	1.25	0.72	0.61	0.53	0.69	0.59	0.52	0.46	0.54	0.48	0.43	0.50	0.45	0.40	0.35	
C	1.5	0.76	0.66	0.59	0.73	0.64	0.57	0.51	0.59	0.53	0.48	0.54	0.49	0.45	0.39	
A	2	0.82	0.73	0.66	0.78	0.71	0.64	0.59	0.65	0.60	0.55	0.60	0.56	0.52	0.45	
	2.5	0.85	0.78	0.72	0.82	0.75	0.69	0.64	0.69	0.64	0.60	0.64	0.60	0.56	0.49	
	3	0.88	0.81	0.75	0.84	0.78	0.73	0.68	0.72	0.68	0.64	0.66	0.63	0.60	0.52	
光源	4	0.91	0.86	0.81	0.88	0.82	0.78	0.74	0.76	0.72	0.69	0.70	0.67	0.64	0.57	
品名: 直管形LEDランプ	5	0.93	0.89	0.84	0.90	0.85	0.82	0.78	0.79	0.76	0.73	0.73	0.70	0.68	0.60	
形式: LDK20SS-N/10/13NA	7	0.96	0.93	0.89	0.93	0.89	0.86	0.83	0.83	0.80	0.78	0.77	0.75	0.73	0.64	
光束: 1,300 lm	10	0.98	0.96	0.93	0.95	0.92	0.90	0.88	0.86	0.84	0.82	0.80	0.78	0.77	0.68	
器具効率 Ft=	単体照度分布(初期値)															
上方光束 Fu=	800 600 400 200															
下方光束 Fd=	0.0 1.0 2.0															
最大取付間隔	A-A 1.40 H															
	B-B 1.24 H															
保守率	良															
	中															
	否															
光度 (cd/1000 lm)	配光曲線 (cd/1000 lm)															
	A-0	B-B	C-0	A'-0	C'-0	180 250 200 150 100 50 0 50 100 150 200 250 180										
0	210	210	210			120 90 60 30 0 30 60 90 120										
10	209	206	207			90 60 30 0 30 60 90 120										
20	203	192	197			60 30 0 30 60 90 120										
30	195	173	183			30 0 30 60 90 120										
40	184	149	166			0 30 60 90 120										
50	168	116	144			0 30 60 90 120										
60	151	81	122			0 30 60 90 120										
70	135	51	102			0 30 60 90 120										
80	116	17	82			0 30 60 90 120										
90	99	1	68			0 30 60 90 120										
100	89	2	53			0 30 60 90 120										
110	69	4	41			0 30 60 90 120										
120	56	6	35			0 30 60 90 120										
130	45	9	29			0 30 60 90 120										
140	35	11	24			0 30 60 90 120										
150	28	13	21			0 30 60 90 120										
160	22	16	19			0 30 60 90 120										
170	18	17	18			0 30 60 90 120										
180	17	17	17			0 30 60 90 120										