


## 日立照明器具 照明特性

|                                                                                         |      |               |      |      |      |      |      |      |      |      |      |      |      |      |      |      |
|-----------------------------------------------------------------------------------------|------|---------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| 名称: 高天井用LEDランプ<br>(E39口金タイプ)                                                            | 反射率  | 天井            | 80%  |      |      | 70%  |      |      |      | 50%  |      |      | 30%  |      |      | 0%   |
|                                                                                         |      | 壁             | 70%  | 50%  | 30%  | 70%  | 50%  | 30%  | 10%  | 50%  | 30%  | 10%  | 50%  | 30%  | 10%  | 0%   |
|                                                                                         |      | 床             | 10%  |      |      |      |      |      |      |      |      |      |      |      |      |      |
| 形式: LME1101MNC                                                                          | 室指数  | 固有照明率 S/H=1.0 |      |      |      |      |      |      |      |      |      |      |      |      |      |      |
| 〈備考〉                                                                                    |      | 0.6           | 0.61 | 0.49 | 0.42 | 0.60 | 0.49 | 0.42 | 0.37 | 0.48 | 0.42 | 0.37 | 0.47 | 0.41 | 0.37 | 0.35 |
| 姿図<br> |      | 0.8           | 0.71 | 0.61 | 0.53 | 0.70 | 0.60 | 0.53 | 0.48 | 0.59 | 0.53 | 0.48 | 0.57 | 0.52 | 0.48 | 0.46 |
|                                                                                         | 1    | 0.78          | 0.68 | 0.61 | 0.76 | 0.67 | 0.61 | 0.56 | 0.66 | 0.60 | 0.56 | 0.65 | 0.59 | 0.55 | 0.53 |      |
|                                                                                         | 1.25 | 0.84          | 0.75 | 0.69 | 0.82 | 0.74 | 0.68 | 0.64 | 0.73 | 0.67 | 0.63 | 0.71 | 0.66 | 0.63 | 0.61 |      |
|                                                                                         | 1.5  | 0.88          | 0.80 | 0.75 | 0.86 | 0.79 | 0.74 | 0.70 | 0.78 | 0.73 | 0.69 | 0.76 | 0.72 | 0.68 | 0.66 |      |
|                                                                                         | 2    | 0.93          | 0.87 | 0.82 | 0.92 | 0.86 | 0.82 | 0.78 | 0.84 | 0.80 | 0.77 | 0.82 | 0.79 | 0.76 | 0.74 |      |
|                                                                                         | 2.5  | 0.96          | 0.91 | 0.87 | 0.95 | 0.90 | 0.86 | 0.82 | 0.88 | 0.84 | 0.81 | 0.86 | 0.83 | 0.80 | 0.78 |      |
|                                                                                         | 3    | 0.98          | 0.94 | 0.90 | 0.97 | 0.92 | 0.89 | 0.86 | 0.90 | 0.87 | 0.85 | 0.89 | 0.86 | 0.84 | 0.81 |      |
| 光源形式                                                                                    | 4    | 1.01          | 0.97 | 0.94 | 0.99 | 0.96 | 0.93 | 0.90 | 0.94 | 0.91 | 0.89 | 0.92 | 0.90 | 0.88 | 0.85 |      |
| -                                                                                       | 5    | 1.02          | 0.99 | 0.97 | 1.01 | 0.98 | 0.96 | 0.94 | 0.96 | 0.94 | 0.92 | 0.94 | 0.92 | 0.91 | 0.88 |      |
| 器具光束                                                                                    | 7    | 1.04          | 1.02 | 1.01 | 1.03 | 1.01 | 1.00 | 0.98 | 0.99 | 0.98 | 0.96 | 0.97 | 0.96 | 0.95 | 0.92 |      |
| 11,500 lm                                                                               | 10   | 1.06          | 1.05 | 1.04 | 1.05 | 1.04 | 1.03 | 1.02 | 1.02 | 1.01 | 1.00 | 0.99 | 0.99 | 0.98 | 0.95 |      |

|                 |     |      |     |      |      |
|-----------------|-----|------|-----|------|------|
| 器具効率 Ft= 100%   |     |      |     |      |      |
| 上方光束 Fu= 0%     |     |      |     |      |      |
| 下方光束 Fd= 100%   |     |      |     |      |      |
|                 |     |      |     |      |      |
| 最大取付間隔          |     |      |     |      |      |
| A-A 1.50        |     | H    |     |      |      |
| B-B             |     | H    |     |      |      |
| 保守率             | 良   | 0.81 |     |      |      |
|                 | 中   | 0.79 |     |      |      |
|                 | 否   | 0.75 |     |      |      |
| 光度 (cd/1000 lm) |     |      |     |      |      |
|                 | A-0 | B-B  | C-0 | A'-0 | C'-0 |
| 0               | 349 |      |     |      |      |
| 10              | 352 |      |     |      |      |
| 20              | 361 |      |     |      |      |
| 30              | 353 |      |     |      |      |
| 40              | 321 |      |     |      |      |
| 50              | 221 |      |     |      |      |
| 60              | 130 |      |     |      |      |
| 70              | 53  |      |     |      |      |
| 80              | 6   |      |     |      |      |
| 90              |     |      |     |      |      |
| 100             |     |      |     |      |      |
| 110             |     |      |     |      |      |
| 120             |     |      |     |      |      |
| 130             |     |      |     |      |      |
| 140             |     |      |     |      |      |
| 150             |     |      |     |      |      |
| 160             |     |      |     |      |      |
| 170             |     |      |     |      |      |
| 180             |     |      |     |      |      |

単体照度分布 (初期値)

単位: 照度 (lx)

0-200  
200-400  
400-600  
600-800  
800-1000

配光曲線 (cd/1000 lm)

単位: 照度 (lx)

0  
30  
60  
90  
120  
150  
180

A  
B  
C-C'