

日立照明器具 照明特性

形式: S250		反射率	天井	80%			70%			50%			30%			0%				
		壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%				
LME1101MN (BK10CLN14A)		床	10%													0%				
姿図		0.6	0.63	0.52	0.45	0.62	0.51	0.45	0.40	0.50	0.44	0.40	0.49	0.44	0.40	0.38				
		0.8	0.73	0.63	0.56	0.72	0.62	0.56	0.51	0.61	0.55	0.51	0.60	0.54	0.50	0.48				
		1	0.79	0.70	0.64	0.78	0.70	0.63	0.59	0.68	0.63	0.58	0.67	0.62	0.58	0.56				
		1.25	0.85	0.77	0.71	0.84	0.76	0.70	0.66	0.74	0.69	0.65	0.73	0.69	0.65	0.63				
		1.5	0.89	0.82	0.77	0.88	0.81	0.76	0.72	0.79	0.75	0.71	0.78	0.74	0.70	0.68				
		2	0.94	0.88	0.84	0.93	0.87	0.83	0.79	0.86	0.82	0.79	0.84	0.81	0.78	0.75				
		2.5	0.97	0.92	0.88	0.96	0.91	0.87	0.84	0.89	0.86	0.83	0.87	0.84	0.82	0.80				
		3	0.99	0.95	0.91	0.97	0.93	0.90	0.87	0.91	0.88	0.86	0.89	0.87	0.85	0.82				
光源		4	1.01	0.98	0.95	1.00	0.97	0.94	0.91	0.95	0.92	0.90	0.92	0.91	0.89	0.86				
品名		5	1.03	1.00	0.98	1.01	0.99	0.97	0.95	0.97	0.95	0.93	0.95	0.93	0.92	0.89				
形式		7	1.05	1.03	1.01	1.04	1.02	1.00	0.99	1.00	0.98	0.97	0.98	0.96	0.95	0.93				
光束		11,600 lm	10	1.06	1.05	1.04	1.05	1.04	1.03	1.02	1.02	1.01	1.00	1.00	0.99	0.98	0.95			
器具効率 Ft= 100.0%		単体照度分布(初期)																		
上方光束 Fu= 0.0%																				
下方光束 Fd= 100.0%																				
配光分類																				
BZ-																				
最大取付間隔																				
A-A 1.44 H																				
B-B H																				
保守率	良	0.81																		
	中	0.79																		
	否	0.75																		
光度(cd/1000 lm)																				
	A-0	B-B	C-0	A'-0	C'-0															
0	370																			
10	390																			
20	400																			
30	374																			
40	314																			
50	223																			
60	110																			
70	41																			
80	5																			
90																				
100																				
110																				
120	1																			
130	1																			
140	1																			
150	1																			
160	2																			
170	3																			
180																				