

## 日立照明器具 照明特性

形式: M400傘あり	反射率	天井	80%			70%			50%			30%			0%																
		壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%															
		床	10%												0%																
室指数		照明率 S/H=1.0																													
姿図	0.6	0.62	0.51	0.44	0.61	0.51	0.44	0.39	0.50	0.44	0.39	0.49	0.43	0.39	0.37																
	0.8	0.72	0.62	0.55	0.71	0.62	0.55	0.50	0.60	0.54	0.50	0.59	0.54	0.50	0.48																
	1	0.79	0.70	0.63	0.78	0.69	0.63	0.58	0.67	0.62	0.58	0.66	0.61	0.57	0.55																
	1.25	0.85	0.76	0.70	0.83	0.76	0.70	0.65	0.74	0.69	0.65	0.72	0.68	0.64	0.62																
	1.5	0.89	0.82	0.76	0.87	0.81	0.75	0.71	0.79	0.74	0.71	0.77	0.73	0.70	0.68																
	2	0.94	0.88	0.83	0.92	0.87	0.83	0.79	0.85	0.81	0.78	0.83	0.80	0.77	0.75																
	2.5	0.97	0.92	0.88	0.95	0.91	0.87	0.83	0.89	0.85	0.82	0.87	0.84	0.81	0.79																
	3	0.99	0.94	0.90	0.97	0.93	0.90	0.87	0.91	0.88	0.85	0.89	0.87	0.84	0.82																
光源		4	1.01	0.98	0.95	1.00	0.96	0.94	0.91	0.94	0.92	0.90	0.92	0.90	0.88	0.86															
品名		5	1.03	1.00	0.97	1.01	0.99	0.96	0.94	0.97	0.95	0.93	0.95	0.93	0.91	0.89															
形式		7	1.05	1.03	1.01	1.03	1.02	1.00	0.99	1.00	0.98	0.97	0.97	0.96	0.95	0.92															
光束		21,500 lm	10	1.06	1.05	1.04	1.05	1.04	1.03	1.02	1.02	1.01	1.00	1.00	0.99	0.98	0.95														
器具効率 Ft= 100.0%		単体照度分布(初期)																													
上方光束 Fu= 0.0%		配光分類																													
下方光束 Fd= 100.0%		BZ-																													
最大取付間隔		A-A 1.42 H																													
B-B H		保良中否																													
光度(cd/1000 lm)		0 373 10 389 20 393 30 369 40 308 50 219 60 119 70 46 80 6 90 100 110 120 130 140 150 1 160 2 170 3 180																													
単体照度分布(初期)																															
配光曲線																															