



日立照明器具 照明特性

名称: 高天井用LEDランプ (E39口金タイプ)	反射率	天井	80%			70%				50%			30%			0%
		壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%
		床	10%													
形式: LMEP1101MNC	室指数	固有照明率 S/H=1.0														
〈備考〉 拡散パネル付		0.6	0.61	0.50	0.42	0.60	0.49	0.42	0.37	0.48	0.42	0.37	0.47	0.41	0.37	0.35
姿図 		0.8	0.71	0.60	0.53	0.69	0.59	0.52	0.47	0.58	0.52	0.47	0.57	0.51	0.47	0.45
	1	0.77	0.67	0.60	0.75	0.66	0.59	0.54	0.65	0.59	0.54	0.63	0.58	0.54	0.52	
	1.25	0.83	0.74	0.67	0.81	0.73	0.66	0.61	0.71	0.65	0.61	0.69	0.65	0.61	0.58	
	1.5	0.87	0.79	0.73	0.85	0.78	0.72	0.67	0.76	0.71	0.67	0.74	0.70	0.66	0.64	
	2	0.92	0.86	0.80	0.91	0.84	0.79	0.75	0.83	0.78	0.74	0.81	0.77	0.74	0.71	
	2.5	0.95	0.90	0.85	0.94	0.88	0.84	0.80	0.86	0.83	0.79	0.84	0.81	0.78	0.76	
	3	0.97	0.92	0.88	0.96	0.91	0.87	0.84	0.89	0.86	0.83	0.87	0.84	0.82	0.79	
光源形式	4	1.00	0.96	0.93	0.99	0.95	0.92	0.89	0.93	0.90	0.87	0.91	0.88	0.86	0.84	
-	5	1.02	0.99	0.96	1.00	0.97	0.95	0.92	0.95	0.93	0.91	0.93	0.91	0.89	0.87	
器具光束	7	1.04	1.02	1.00	1.03	1.01	0.99	0.97	0.98	0.97	0.95	0.96	0.95	0.94	0.91	
10,700 lm	10	1.06	1.04	1.03	1.05	1.03	1.02	1.01	1.01	1.00	0.99	0.99	0.98	0.97	0.94	

器具効率 Ft= 100%		
上方光束 Fu= 0%		
下方光束 Fd= 100%		
最大取付間隔		
A-A		1.20 H
B-B		H
保守率	良	0.81
	中	0.79
	否	0.75

光度 (cd/1000 lm)					
	A-0	B-B	C-0	A'-0	C'-0
0	406				
10	398				
20	376				
30	328				
40	263				
50	204				
60	137				
70	78				
80	29				
90					
100					
110					
120					
130					
140					
150					
160					
170					
180					


単体照度分布 (初期値)



0-200
200-400
400-600
600-800
800-1000

A← 水平距離(m) →B

配光曲線 (cd/1000 lm)



A
B
C-C'