

日立照明器具 照明特性

形式：MK10011+NH660FL		反 射 率	天井	80%			70%				50%			30%			0%		
<広照形>			壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%		
			床	10%															0%
			室指数	照明率 S/H=1.0															
姿図 		0.6	0.55	0.49	0.44	0.55	0.48	0.44	0.41	0.47	0.44	0.41	0.47	0.43	0.41	0.39			
		0.8	0.63	0.56	0.52	0.62	0.56	0.52	0.49	0.55	0.52	0.49	0.54	0.51	0.49	0.47			
		1	0.67	0.61	0.58	0.66	0.61	0.57	0.54	0.60	0.57	0.54	0.59	0.56	0.54	0.52			
		1.25	0.70	0.66	0.62	0.69	0.65	0.62	0.59	0.64	0.61	0.59	0.63	0.60	0.58	0.57			
		1.5	0.73	0.69	0.66	0.72	0.68	0.65	0.63	0.67	0.64	0.62	0.66	0.63	0.61	0.60			
		2	0.76	0.73	0.70	0.75	0.72	0.69	0.67	0.71	0.68	0.67	0.69	0.67	0.66	0.64			
		2.5	0.78	0.75	0.72	0.77	0.74	0.72	0.70	0.72	0.71	0.69	0.71	0.69	0.68	0.66			
		3	0.79	0.76	0.74	0.78	0.75	0.73	0.72	0.74	0.72	0.70	0.72	0.71	0.69	0.68			
光源		4	0.80	0.78	0.76	0.79	0.77	0.75	0.74	0.75	0.74	0.73	0.74	0.73	0.72	0.70			
品名	高圧ナトリウムランプ	5	0.81	0.79	0.78	0.80	0.78	0.77	0.76	0.77	0.76	0.75	0.75	0.74	0.73	0.71			
形式	NH660FL	7	0.82	0.81	0.80	0.81	0.80	0.79	0.78	0.78	0.78	0.77	0.77	0.76	0.76	0.73			
光束	90,500 lm	10	0.83	0.83	0.82	0.82	0.82	0.81	0.81	0.80	0.79	0.79	0.78	0.78	0.77	0.75			

器具効率 $F_t = 77.7\%$
 上方光束 $F_u = 1.0\%$
 下方光束 $F_d = 76.8\%$

配光分類

BZ-

最大取付間隔

A-A 1.20 H


B-B H

保守率	良	0.78
	中	0.74
	否	0.65

光度 (cd/1000 lm)

	A-0	B-B	C-0
0	455		
10	475		
20	441		
30	364		
40	246		
50	119		
60	27		
70	4		
80	1		
90	1		
100	1		
110	1		
120	2		
130	2		
140	2		
150	2		
160	2		
170	2		
180	2		

単体照度分布(初期)



配光曲線

