



日立照明器具 照明特性

名称: 高天井用LED器具	反 射 率	天井	80%			70%				50%			30%			0%
		壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%
		床	10%													0%
形式: MTE1403MN-Z14B	室指数		固有照明率 S/H=1.0													
<備考> 水銀ランプ400クラス ビームの開き角: 90°	0.6	0.66	0.55	0.49	0.64	0.55	0.48	0.44	0.54	0.48	0.44	0.53	0.48	0.44	0.42	
		0.8	0.76	0.66	0.60	0.74	0.66	0.59	0.55	0.64	0.59	0.55	0.63	0.58	0.55	0.53
姿図 	1	0.82	0.73	0.67	0.81	0.73	0.67	0.63	0.71	0.66	0.62	0.70	0.66	0.62	0.60	
	1.25	0.87	0.80	0.74	0.86	0.79	0.74	0.70	0.78	0.73	0.69	0.76	0.72	0.69	0.67	
	1.5	0.91	0.85	0.80	0.90	0.84	0.79	0.75	0.82	0.78	0.75	0.81	0.77	0.74	0.72	
	2	0.96	0.91	0.86	0.94	0.90	0.86	0.82	0.88	0.85	0.82	0.86	0.83	0.81	0.79	
	2.5	0.98	0.94	0.90	0.97	0.93	0.90	0.87	0.91	0.88	0.86	0.89	0.87	0.85	0.82	
	3	1.00	0.96	0.93	0.99	0.95	0.92	0.89	0.93	0.91	0.88	0.91	0.89	0.87	0.85	
	4	1.02	0.99	0.96	1.01	0.98	0.96	0.93	0.96	0.94	0.92	0.94	0.92	0.91	0.88	
	5	1.04	1.01	0.99	1.02	1.00	0.98	0.96	0.98	0.96	0.95	0.96	0.95	0.93	0.91	
光源形式	7	1.06	1.04	1.02	1.04	1.03	1.01	1.00	1.01	0.99	0.98	0.99	0.98	0.97	0.94	
LED	10	1.07	1.06	1.05	1.06	1.05	1.04	1.03	1.03	1.02	1.01	1.01	1.00	0.99	0.97	
器具光束																
13,500 lm																
器具効率 Ft=	100%															
上方光束 Fu=	0.0%															
下方光束 Fd=	100.0%															
最大取付間隔																
A-A	1.40	H														
B-B		H														
保守率	良	0.81														
	中	0.79														
	否	0.75														
光度 (cd/1000 lm)																
	A-0	B-B	C-0	A'-0	C'-0											
0	386															
10	419															
20	498															
30	386															
40	304															
50	223															
60	104															
70	15															
80	1															
90																
100																
110																
120																
130																
140																
150																
160																
170																
180																

単体照度分布 (初期値)



配光曲線
(cd/1000 lm)

