



日立照明器具 照明特性

名称: 高天井用LED器具	反射率	天井	80%			70%				50%			30%			0%
		壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%
		床	10%													0%
形式: MTE1403NN-Z14B	室指数	固有照明率 S/H=1.0														
<備考> 水銀ランプ 400クラス ビームの開き角: 60° 姿図 		0.6	0.79	0.72	0.68	0.79	0.72	0.68	0.65	0.71	0.67	0.64	0.71	0.67	0.64	0.63
		0.8	0.87	0.81	0.76	0.86	0.80	0.76	0.73	0.79	0.76	0.73	0.78	0.75	0.73	0.71
	1	0.91	0.86	0.82	0.90	0.85	0.81	0.79	0.84	0.81	0.78	0.83	0.80	0.78	0.76	
	1.25	0.95	0.90	0.86	0.94	0.89	0.86	0.83	0.88	0.85	0.83	0.87	0.84	0.82	0.81	
	1.5	0.97	0.93	0.90	0.96	0.92	0.89	0.87	0.91	0.88	0.86	0.90	0.88	0.86	0.84	
	2	1.00	0.97	0.94	0.99	0.96	0.94	0.91	0.95	0.93	0.91	0.93	0.91	0.90	0.88	
	2.5	1.02	0.99	0.97	1.01	0.98	0.96	0.94	0.97	0.95	0.93	0.95	0.93	0.92	0.90	
	3	1.03	1.00	0.98	1.02	0.99	0.97	0.96	0.98	0.96	0.94	0.96	0.95	0.93	0.91	
	光源形式	4	1.04	1.02	1.00	1.03	1.01	1.00	0.98	0.99	0.98	0.97	0.98	0.96	0.95	0.93
	LED	5	1.05	1.04	1.02	1.04	1.03	1.01	1.00	1.01	0.99	0.98	0.99	0.98	0.97	0.95
器具光束	7	1.07	1.05	1.04	1.05	1.04	1.04	1.03	1.02	1.02	1.01	1.01	1.00	0.99	0.97	
14,200 lm	10	1.08	1.07	1.06	1.07	1.06	1.05	1.05	1.04	1.03	1.03	1.02	1.02	1.01	0.99	

器具効率 Ft= 100%		
上方光束 Fu= 0.0%		
下方光束 Fd= 100.0%		
最大取付間隔		
A-A 0.94		H
B-B		H
保守率	良	0.81
	中	0.79
	否	0.75


光度 (cd/1000 lm)					
	A-0	B-B	C-0	A'-0	C'-0
0	933				
10	889				
20	760				
30	500				
40	245				
50	70				
60	17				
70	5				
80	2				
90					
100					
110					
120					
130					
140					
150					
160					
170					
180					

単体照度分布 (初期値)



A← 水平距離(m) →B

配光曲線
(cd/1000 lm)



— A
- - - B
· · · C-C'