

日立照明器具 照明特性

名称: 高天井用LED器具	反射率	天井	80%			70%			50%			30%			0%			
		壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%			
		床	10%												0%			
形式: MTE1403WN-J14B	室指数	固有照明率 S/H=1.0																
<備考> 水銀ランプ400クラス ビームの開き角: 110°	0.6	0.60	0.49	0.41	0.59	0.48	0.41	0.36	0.47	0.40	0.36	0.46	0.40	0.36	0.34			
	0.8	0.70	0.60	0.52	0.69	0.59	0.52	0.47	0.58	0.51	0.47	0.56	0.51	0.46	0.44			
姿図	1	0.77	0.67	0.60	0.76	0.66	0.60	0.55	0.65	0.59	0.54	0.63	0.58	0.54	0.52			
	1.25	0.83	0.74	0.68	0.82	0.73	0.67	0.62	0.72	0.66	0.62	0.70	0.65	0.61	0.59			
	1.5	0.87	0.80	0.74	0.86	0.79	0.73	0.69	0.77	0.72	0.68	0.75	0.71	0.67	0.65			
	2	0.93	0.87	0.82	0.92	0.86	0.81	0.77	0.84	0.80	0.76	0.82	0.78	0.75	0.73			
	2.5	0.96	0.91	0.86	0.95	0.90	0.86	0.82	0.88	0.84	0.81	0.86	0.83	0.80	0.78			
	3	0.98	0.93	0.89	0.97	0.92	0.89	0.85	0.90	0.87	0.84	0.88	0.86	0.83	0.81			
光源形式		4	1.01	0.97	0.94	0.99	0.96	0.93	0.90	0.94	0.91	0.89	0.92	0.90	0.88	0.85		
LED		5	1.03	1.00	0.97	1.01	0.98	0.96	0.94	0.96	0.94	0.92	0.94	0.92	0.91	0.88		
器具光束		7	1.05	1.03	1.01	1.03	1.02	1.00	0.98	0.99	0.98	0.96	0.97	0.96	0.95	0.92		
13,500 lm		10	1.06	1.05	1.04	1.05	1.04	1.03	1.02	1.02	1.01	1.00	1.00	0.99	0.98	0.95		
器具効率 Ft= 100%			単体照度分布(初期値)															
上方光束 Fu= 0.0%			10.0															
下方光束 Fd= 100.0%			5.0															
最大取付間隔			0.0															
A-A 1.34 H			-5.0															
B-B H			5.0															
保守率 良 0.81			10.0															
中 0.79			A← 水平距離(m) →B															
否 0.75			10.0															
光度(cd/1000 lm)			配光曲線															
A	A-0	B-B	C-0	A'-0	C'-0	(cd/1000 lm)												
0	366					180	400.0	350.0	300.0	250.0	200.0	150.0	100.0	50.0	0.0			
10	362					150												
20	349					120												
30	325					90												
40	292					60												
50	234					30												
60	158					0												
70	60																	
80	4																	
90																		
100																		
110																		
120																		
130																		
140																		
150																		
160																		
170																		
180																		