



日立照明器具 照明特性

名称: 高天井用LED器具	天井 反射率	80%			70%				50%			30%			0%		
		壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%	
形式: MTE17AWN-X14B	床	10%															0%
		室指数	固有照明率 S/H=1.0														
〈備考〉	0.6	0.57	0.45	0.37	0.55	0.44	0.37	0.31	0.43	0.36	0.31	0.41	0.35	0.31	0.29		
	0.8	0.66	0.55	0.47	0.65	0.54	0.46	0.41	0.52	0.46	0.40	0.51	0.45	0.40	0.38		
姿図 	1	0.73	0.62	0.54	0.71	0.61	0.54	0.48	0.59	0.52	0.47	0.57	0.51	0.47	0.44		
	1.25	0.79	0.69	0.61	0.77	0.68	0.61	0.55	0.65	0.59	0.54	0.63	0.58	0.54	0.5		
	1.5	0.83	0.74	0.67	0.81	0.73	0.66	0.61	0.71	0.65	0.60	0.68	0.63	0.59	0.56		
	2	0.89	0.81	0.75	0.87	0.80	0.74	0.70	0.77	0.73	0.68	0.75	0.71	0.67	0.64		
	2.5	0.92	0.86	0.80	0.90	0.84	0.79	0.75	0.82	0.77	0.74	0.79	0.75	0.72	0.69		
	3	0.95	0.89	0.84	0.93	0.87	0.83	0.79	0.85	0.81	0.77	0.82	0.79	0.76	0.72		
	4	0.98	0.93	0.89	0.96	0.92	0.88	0.85	0.89	0.86	0.83	0.86	0.83	0.81	0.77		
光源形式 —	5	1.00	0.96	0.93	0.98	0.95	0.91	0.88	0.92	0.89	0.86	0.89	0.86	0.84	0.81		
	器具光束 18,000 lm	7	1.02	1.00	0.97	1.01	0.98	0.96	0.93	0.95	0.93	0.91	0.92	0.91	0.89	0.85	
10		1.04	1.02	1.01	1.02	1.01	0.99	0.98	0.98	0.96	0.95	0.95	0.94	0.93	0.89		
器具効率 Ft= 100%		単体照度分布 (初期値) 															
上方光束 Fu= 3.6%																	
下方光束 Fd= 96.4%																	
最大取付間隔																	
A-A 1.32 H																	
B-B 1.32 H																	
保守率	良	0.83															
	中	0.81															
	否	0.76															
光度 (cd/1000 lm)																	
	A-0	B-B	C-0	A'-0	C'-0												
0	311	311	311														
10	307	307	307														
20	297	298	295														
30	274	277	279														
40	243	241	233														
50	208	209	195														
60	160	162	142														
70	102	95	104														
80	38	37	54														
90	6	6	6														
100	6	5	3														
110	13	14	9														
120	9	9	5														
130	6		8														
140	7		5														
150	4		3														
160																	
170																	
180																	
配光曲線 (cd/1000 lm)		