


日立照明器具 照明特性

形式: MTE2203NN 〈メタルハライドランプ 400クラス〉 〈ビームの開き: 60度〉	反 射 率	天井	80%			70%				50%			30%			0%
		壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%
		床	10%													0%
		室指数	照明率 S/H=1.0													
姿図 		0.6	0.80	0.73	0.69	0.80	0.73	0.69	0.66	0.72	0.68	0.66	0.72	0.68	0.66	0.64
		0.8	0.88	0.82	0.77	0.87	0.81	0.77	0.74	0.80	0.77	0.74	0.79	0.76	0.74	0.73
		1	0.92	0.86	0.83	0.91	0.86	0.82	0.79	0.85	0.82	0.79	0.84	0.81	0.79	0.77
		1.25	0.95	0.91	0.87	0.94	0.90	0.87	0.84	0.89	0.86	0.84	0.88	0.85	0.83	0.82
		1.5	0.98	0.94	0.90	0.97	0.93	0.90	0.88	0.92	0.89	0.87	0.90	0.88	0.86	0.85
		2	1.01	0.97	0.95	1.00	0.97	0.94	0.92	0.95	0.93	0.91	0.94	0.92	0.90	0.89
		2.5	1.02	0.99	0.97	1.01	0.99	0.96	0.94	0.97	0.95	0.93	0.95	0.94	0.92	0.91
		3	1.03	1.01	0.99	1.02	1.00	0.98	0.96	0.98	0.96	0.95	0.96	0.95	0.94	0.92
		4	1.04	1.02	1.01	1.03	1.01	1.00	0.98	1.00	0.98	0.97	0.98	0.97	0.96	0.93
		5	1.05	1.04	1.02	1.04	1.03	1.01	1.00	1.01	1.00	0.99	0.99	0.98	0.97	0.95
光源																
品名	LED															
形式	LED															
光束	21,900 lm															

器具効率 Ft= 100.0%
 上方光束 Fu= 0.0%
 下方光束 Fd= 100.0%

配光分類
BZ-


最大取付間隔
 A-A 0.96 H
 B-B H

保守率	良	0.79
	中	0.75
	否	0.71

光度 (cd/1000 lm)

	A-0	B-B	C-0
0	932		
10	896		
20	766		
30	512		
40	241		
50	66		
60	16		
70	5		
80			
90			
100			
110			
120			
130			
140			
150			
160			
170			
180			

単体照度分布(初期)



配光曲線

