

日立照明器具 照明特性

形式: MTE2701NN		天井	80%			70%				50%			30%			0%
		壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%
		床	10%													0%
		室指数	照明率 S/H=1.0													
		0.6	0.83	0.76	0.72	0.82	0.76	0.72	0.70	0.75	0.72	0.69	0.75	0.72	0.69	0.68
		0.8	0.90	0.84	0.80	0.89	0.84	0.80	0.77	0.83	0.80	0.77	0.82	0.79	0.77	0.76
		1	0.93	0.89	0.85	0.93	0.88	0.85	0.82	0.87	0.84	0.82	0.86	0.83	0.81	0.80
		1.25	0.97	0.92	0.89	0.96	0.92	0.89	0.86	0.90	0.88	0.86	0.89	0.87	0.85	0.84
		1.5	0.99	0.95	0.92	0.98	0.94	0.92	0.89	0.93	0.91	0.89	0.92	0.90	0.88	0.87
		2	1.01	0.98	0.96	1.00	0.98	0.95	0.94	0.96	0.94	0.93	0.95	0.93	0.92	0.90
		2.5	1.03	1.00	0.98	1.02	0.99	0.97	0.96	0.98	0.96	0.95	0.96	0.95	0.94	0.92
		3	1.04	1.01	0.99	1.03	1.00	0.99	0.97	0.99	0.97	0.96	0.97	0.96	0.95	0.93
光源		4	1.05	1.03	1.01	1.04	1.02	1.00	0.99	1.00	0.99	0.98	0.98	0.97	0.96	0.94
品名 LED		5	1.06	1.04	1.03	1.05	1.03	1.02	1.01	1.01	1.00	0.99	0.99	0.99	0.98	0.96
形式 LED		7	1.07	1.06	1.05	1.06	1.05	1.04	1.03	1.03	1.02	1.02	1.01	1.00	1.00	0.97
光束 28,000 lm		10	1.08	1.07	1.07	1.07	1.06	1.06	1.05	1.04	1.04	1.03	1.02	1.02	1.02	0.99

器具効率 Ft= 100.0%
 上方光束 Fu= 0.0%
 下方光束 Fd= 100.0%

配光分類
BZ-

最大取付間隔

A-A 0.94 H


B-B 0.02 H

保守率	良	0.79
	中	0.75
	否	0.71

光度 (cd/1000 lm)

	A-0	B-B	C-0
0	1010		
10	1032		
20	866		
30	491		
40	211		
50	43		
60	6		
70	4		
80	1		
90			
100			
110			
120			
130			
140			
150			
160			
170			
180			

単体照度分布(初期)



配光曲線

