



日立照明器具 照明特性

名称: 高天井用LED器具		反射率	天井	80%			70%			50%			30%			0%	
			壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%
形式: MTE28ANN-J24A		室指数	床	10%													0%
			固有照明率 S/H=1.0														
<備考> 配光角(中角)		0.6	0.80	0.73	0.68	0.79	0.72	0.68	0.65	0.72	0.68	0.65	0.71	0.67	0.65	0.64	
		0.8	0.87	0.81	0.77	0.86	0.81	0.77	0.74	0.80	0.76	0.73	0.79	0.76	0.73	0.72	
姿図 		1	0.91	0.86	0.82	0.90	0.85	0.82	0.79	0.84	0.81	0.79	0.83	0.80	0.78	0.77	
		1.25	0.95	0.90	0.87	0.94	0.90	0.86	0.84	0.88	0.85	0.83	0.87	0.85	0.83	0.81	
		1.5	0.97	0.93	0.90	0.96	0.93	0.90	0.87	0.91	0.89	0.86	0.90	0.88	0.86	0.84	
		2	1.00	0.97	0.94	0.99	0.96	0.94	0.92	0.95	0.93	0.91	0.93	0.92	0.90	0.88	
		2.5	1.02	0.99	0.97	1.01	0.98	0.96	0.94	0.97	0.95	0.93	0.95	0.93	0.92	0.90	
		3	1.03	1.00	0.98	1.02	0.99	0.97	0.96	0.98	0.96	0.94	0.96	0.95	0.93	0.91	
		4	1.04	1.02	1.00	1.03	1.01	0.99	0.98	0.99	0.98	0.97	0.98	0.96	0.95	0.93	
光源形式		5	1.05	1.03	1.02	1.04	1.02	1.01	1.00	1.01	0.99	0.98	0.99	0.98	0.97	0.95	
		7	1.06	1.05	1.04	1.05	1.04	1.03	1.03	1.02	1.02	1.01	1.00	1.00	0.99	0.97	
器具光束 28,000 lm		10	1.07	1.07	1.06	1.06	1.06	1.05	1.05	1.04	1.03	1.03	1.02	1.01	1.01	0.98	

器具効率 Ft= 100%					
上方光束 Fu= 0%					
下方光束 Fd= 100%					
最大取付間隔					
A-A		0.94	H		
B-B		0.96	H		
保守率	良	0.81			
	中	0.79			
	否	0.75			
光度 (cd/1000 lm)					
	A-0	B-B	C-0	A'-0	C'-0
0	938	938	938		
10	886	897	911		
20	740	727	778		
30	511	527	505		
40	251	242	245		
50	62	62	67		
60	14	14	15		
70	4	3	3		
80	1	1	1		
90					
100					
110					
120					
130					
140					
150					
160					
170					
180					

単体照度分布(初期値)



配光曲線
(cd/1000 lm)

