

日立照明器具 照明特性

名称: 交換形LED逆富士形	天井	80%			70%				50%			30%			0%	
		壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%
			床	10%												
形式: NC4BCP	室指数	固有照明率 S/H=1.0														
<備考> キャパシタ付	0.6	0.57	0.45	0.37	0.55	0.44	0.37	0.31	0.43	0.36	0.31	0.41	0.35	0.31	0.29	
	0.8	0.66	0.55	0.47	0.64	0.54	0.46	0.41	0.52	0.45	0.40	0.50	0.44	0.40	0.37	
姿図	1	0.72	0.61	0.54	0.71	0.60	0.53	0.47	0.58	0.52	0.47	0.56	0.51	0.46	0.43	
	1.25	0.78	0.68	0.61	0.76	0.67	0.60	0.54	0.65	0.58	0.53	0.63	0.57	0.53	0.50	
	1.5	0.82	0.73	0.66	0.80	0.72	0.65	0.60	0.70	0.64	0.59	0.67	0.62	0.58	0.55	
	2	0.88	0.80	0.74	0.86	0.79	0.73	0.68	0.76	0.71	0.67	0.74	0.69	0.66	0.63	
	2.5	0.91	0.85	0.79	0.89	0.83	0.78	0.73	0.80	0.76	0.72	0.78	0.74	0.71	0.67	
	3	0.94	0.88	0.83	0.92	0.86	0.81	0.77	0.83	0.79	0.76	0.81	0.77	0.74	0.71	
	4	0.97	0.92	0.88	0.95	0.90	0.86	0.83	0.87	0.84	0.81	0.85	0.82	0.79	0.76	
光源形式	5	0.99	0.95	0.91	0.97	0.93	0.90	0.87	0.90	0.87	0.85	0.88	0.85	0.83	0.79	
器具光束	7	1.01	0.98	0.96	1.00	0.97	0.94	0.92	0.94	0.92	0.90	0.91	0.89	0.88	0.84	
7,200 lm	10	1.03	1.01	0.99	1.02	1.00	0.98	0.96	0.97	0.95	0.94	0.94	0.93	0.91	0.88	

器具効率 Ft= 100%					
上方光束 Fu= 3.4%					
下方光束 Fd= 96.6%					
最大取付間隔					
A-A		1.26 H			
B-B		1.24 H			
保守率	良	0.88			
	中	0.86			
	否	0.81			
光度 (cd/1000 lm)					
	A-0	B-B	C-0	A'-0	C'-0
0	326	326	326		
10	319	320	319		
20	300	298	299		
30	274	267	270		
40	240	228	234		
50	198	178	188		
60	156	129	143		
70	117	79	100		
80	79	28	59		
90	51	1	32		
100	32	1	15		
110	6	1	1		
120					
130					
140					
150					
160					
170					
180					

単体照度分布 (初期値)

単位: 照度 (lx)

0-200
200-400
400-600
600-800
800-1000

配光曲線 (cd/1000 lm)

単位: 配光 (cd/1000 lm)

0-50
50-100
100-150
150-200
200-250
250-300
300-350