


日立照明器具 照明特性

名称:交換形LED下面開放	反 射 率	天井	80%			70%				50%			30%			0%
		壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%
		床	10%													
形式:NC4C	室指数	固有照明率 S/H=1.0														
〈備考〉	0.6	0.57	0.45	0.37	0.56	0.44	0.37	0.32	0.43	0.36	0.31	0.42	0.36	0.31	0.29	
	0.8	0.66	0.55	0.47	0.65	0.54	0.47	0.41	0.53	0.46	0.41	0.51	0.45	0.41	0.38	
姿図 	1	0.73	0.62	0.54	0.71	0.61	0.54	0.48	0.59	0.53	0.48	0.58	0.52	0.47	0.45	
	1.25	0.79	0.69	0.61	0.77	0.68	0.61	0.55	0.66	0.60	0.55	0.64	0.59	0.54	0.52	
	1.5	0.83	0.74	0.67	0.81	0.73	0.67	0.61	0.71	0.65	0.61	0.69	0.64	0.60	0.58	
	2	0.89	0.81	0.75	0.87	0.80	0.75	0.70	0.78	0.73	0.69	0.76	0.72	0.68	0.66	
	2.5	0.92	0.86	0.80	0.91	0.85	0.80	0.75	0.83	0.78	0.74	0.80	0.77	0.73	0.71	
	3	0.95	0.89	0.84	0.93	0.88	0.83	0.79	0.86	0.82	0.78	0.83	0.80	0.77	0.74	
	光源形式	4	0.98	0.93	0.89	0.96	0.92	0.88	0.85	0.90	0.87	0.84	0.88	0.85	0.82	0.80
CE402NA-J14	5	1.00	0.96	0.93	0.98	0.95	0.92	0.89	0.93	0.90	0.87	0.90	0.88	0.86	0.83	
器具光束	7	1.02	1.00	0.97	1.01	0.98	0.96	0.94	0.96	0.94	0.92	0.94	0.92	0.91	0.88	
2,680 lm	10	1.04	1.02	1.01	1.03	1.01	1.00	0.98	0.99	0.98	0.96	0.97	0.96	0.94	0.92	


器具効率 F_t	100%
上方光束 F_u	0%
下方光束 F_d	100%

最大取付間隔		
A-A	1.28	H
B-B	1.28	H

保守率	良	0.86
	中	0.81
	否	0.72

光 度 (cd/1000 lm)				3.0 	
	A-0	B-B	C-0	A'-0	C'-0
0	325	325	325		
10	319	322	321		
20	304	304	304		
30	277	279	283		
40	248	244	247		
50	208	198	201		
60	166	148	156		
70	120	92	112		
80	61	33	52		
90	10		2		
100					
110					
120					
130					
140					
150					
160					
170					
180					

単体照度分布(初期値)



配光曲線
(cd/1000 lm)

