

日立照明器具 照明特性

形式: NE32401W-JZU14		天井 反射率 壁 床 室指数	80%			70%				50%			30%			0%	
<高出力タイプ> <白色相当> <照度補正、連続調光共用形>			70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%	
			10%														0%
			照明率 S/H=1.0														
姿図 		0.6	0.58	0.46	0.38	0.57	0.45	0.38	0.33	0.44	0.37	0.33	0.43	0.37	0.32	0.31	
		0.8	0.68	0.56	0.48	0.66	0.56	0.48	0.43	0.54	0.47	0.42	0.53	0.47	0.42	0.40	
		1	0.74	0.63	0.56	0.73	0.63	0.55	0.50	0.61	0.55	0.49	0.59	0.54	0.49	0.47	
		1.25	0.80	0.70	0.63	0.79	0.69	0.63	0.57	0.68	0.62	0.57	0.66	0.61	0.56	0.54	
		1.5	0.85	0.76	0.69	0.83	0.75	0.68	0.63	0.73	0.67	0.63	0.71	0.66	0.62	0.60	
		2	0.90	0.83	0.77	0.89	0.82	0.77	0.72	0.80	0.75	0.71	0.78	0.74	0.70	0.68	
		2.5	0.94	0.88	0.82	0.92	0.86	0.82	0.77	0.84	0.80	0.76	0.82	0.79	0.75	0.73	
		3	0.96	0.91	0.86	0.94	0.89	0.85	0.81	0.87	0.83	0.80	0.85	0.82	0.79	0.76	
光源		4	0.99	0.95	0.91	0.98	0.94	0.90	0.87	0.91	0.88	0.85	0.89	0.87	0.84	0.82	
品名	LED	5	1.01	0.98	0.94	1.00	0.96	0.93	0.91	0.94	0.92	0.89	0.92	0.90	0.88	0.85	
形式		7	1.04	1.01	0.99	1.02	1.00	0.98	0.96	0.98	0.96	0.94	0.95	0.94	0.92	0.90	
光束	7,910 lm	10	1.05	1.04	1.02	1.04	1.02	1.01	0.99	1.00	0.99	0.98	0.98	0.97	0.96	0.93	

器具効率 Ft= 100.0%				単体照度分布(初期) 0-200 200-400 400-600 600-800 800-1000											
上方光束 Fu= 0.0%															
下方光束 Fd= 100.0%															
配光分類															
BZ-															
最大取付間隔															
A-A 1.32 H															
B-B 1.22 H															
保守率	良	0.81													
	中	0.77													
	否	0.68													
光度 (cd/1000 lm)															
	A-0	B-B	C-0	A'-0	C'-0										
0	342	342	342												
10	338	333	337												
20	321	310	316												
30	302	279	293												
40	271	237	257												
50	231	189	214												
60	175	133	165												
70	114	82	106												
80	38	30	40												
90															
100															
110															
120															
130															
140															
150															
160															
170															
180															

配光曲線			
A B C-C'			