



日立照明器具 照明特性

形式：NE45401L-JZU14A		反 射 率	天井	80%			70%				50%			30%			0%	
<高出力タイプ>			壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%	
<電球色相当>			床	10%														0%
<初期照度補正、連続調光共用形>			室指数	照明率 S/H=1.0														
姿図 		0.6	0.58	0.46	0.38	0.57	0.45	0.38	0.33	0.44	0.38	0.33	0.43	0.37	0.33	0.31		
		0.8	0.68	0.56	0.49	0.66	0.56	0.48	0.43	0.54	0.48	0.43	0.53	0.47	0.42	0.40		
		1	0.74	0.64	0.56	0.73	0.63	0.56	0.50	0.61	0.55	0.50	0.60	0.54	0.49	0.47		
		1.25	0.80	0.71	0.63	0.79	0.70	0.63	0.58	0.68	0.62	0.57	0.66	0.61	0.57	0.54		
		1.5	0.85	0.76	0.69	0.83	0.75	0.69	0.64	0.73	0.68	0.63	0.72	0.67	0.63	0.60		
		2	0.91	0.83	0.78	0.89	0.82	0.77	0.72	0.80	0.76	0.72	0.78	0.74	0.71	0.68		
		2.5	0.94	0.88	0.83	0.92	0.87	0.82	0.78	0.85	0.80	0.77	0.83	0.79	0.76	0.73		
		3	0.96	0.91	0.86	0.95	0.90	0.85	0.82	0.88	0.84	0.81	0.85	0.82	0.79	0.77		
光源		4	0.99	0.95	0.91	0.98	0.94	0.90	0.87	0.92	0.89	0.86	0.89	0.87	0.85	0.82		
品名	LED	5	1.01	0.98	0.95	1.00	0.97	0.94	0.91	0.94	0.92	0.89	0.92	0.90	0.88	0.85		
形式		7	1.04	1.01	0.99	1.02	1.00	0.98	0.96	0.98	0.96	0.94	0.96	0.94	0.93	0.90		
光束	11,020 lm	10	1.05	1.04	1.02	1.04	1.03	1.01	1.00	1.00	0.99	0.98	0.98	0.97	0.96	0.93		

器具効率 Ft= 100.0%		
上方光束 Fu= 0.0%		
下方光束 Fd= 100.0%		
配光分類		
BZ-		
最大取付間隔		
A-A	1.34	H
B-B	1.22	H
保守率	良	0.86
	中	0.81
	否	0.72

単体照度分布(初期)



光度 (cd/1000 lm)					
	A-0	B-B	C-0	A'-0	C'-0
0	342	342	342		
10	335	333	333		
20	324	313	318		
30	307	279	295		
40	278	236	261		
50	233	191	219		
60	175	135	165		
70	102	81	108		
80	23	32	36		
90					
100					
110					
120					
130					
140					
150					
160					
170					
180					

配光曲線

