

日立照明器具 照明特性

名称: 直管形LED搭載器具	天井	反射率	80%			70%				50%			30%			0%			
			壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%		
				床	10%														0%
形式: NKE2290-J14AA	室指数		照明率 S/H=1.0																
<備考>	0.6	0.49	0.38	0.31	0.48	0.37	0.30	0.25	0.36	0.30	0.25	0.35	0.29	0.25	0.23				
	0.8	0.57	0.46	0.39	0.56	0.46	0.39	0.33	0.44	0.38	0.33	0.43	0.37	0.33	0.31				
姿図 	1	0.63	0.53	0.45	0.62	0.52	0.45	0.39	0.50	0.44	0.39	0.49	0.43	0.38	0.36				
	1.25	0.68	0.59	0.51	0.67	0.58	0.51	0.46	0.56	0.50	0.45	0.54	0.49	0.44	0.42				
	1.5	0.72	0.64	0.57	0.71	0.62	0.56	0.51	0.60	0.55	0.50	0.59	0.54	0.50	0.47				
	2	0.78	0.70	0.64	0.76	0.69	0.63	0.58	0.67	0.62	0.58	0.65	0.60	0.57	0.54				
	2.5	0.81	0.74	0.69	0.79	0.73	0.68	0.63	0.71	0.66	0.62	0.69	0.65	0.62	0.59				
	3	0.83	0.77	0.72	0.82	0.76	0.71	0.67	0.74	0.70	0.66	0.72	0.68	0.65	0.62				
	4	0.86	0.81	0.77	0.85	0.80	0.76	0.73	0.78	0.74	0.71	0.76	0.73	0.70	0.67				
光源	5	0.88	0.84	0.81	0.87	0.83	0.80	0.77	0.81	0.78	0.75	0.78	0.76	0.74	0.71				
品名 直管形LEDランプ	7	0.91	0.88	0.85	0.89	0.87	0.84	0.82	0.84	0.82	0.80	0.82	0.80	0.78	0.75				
形式 LDK20SS-D/10/12NA	10	0.93	0.91	0.89	0.91	0.89	0.87	0.86	0.87	0.85	0.84	0.85	0.84	0.82	0.79				
光束 2,520 lm																			
器具効率 Ft= 89.6%		単体照度分布(初期値) 0-200 200-400 400-600 600-800 800-1000																	
上方光束 Fu= 1.0%																			
下方光束 Fd= 88.5%																			
最大取付間隔																			
A-A 1.38 H																			
B-B 1.26 H																			
保守率	良	0.86																	
	中	0.81																	
	否	0.72																	
光度 (cd/1000 lm)		配光曲線 (cd/1000 lm) A B C-C'																	
	A-0															B-B	C-0	A'-0	C'-0
0	253															253	253		
10	251															250	250		
20	244															236	239		
30	234															212	225		
40	214															182	201		
50	191															144	171		
60	170															107	141		
70	147															65	118		
80	99															22	82		
90	26																29		
100	1																2		
110																			
120																			
130																			
140																			
150																			
160																			
170																			
180																			