

日立照明器具 照明特性															
名称: 直管形LED搭載器具	反射率	天井	80%				70%				50%				
	壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	
形式: NKE4105-JM14AE	床	10%												0%	
室指数	照明率 S/H=1.0														
<備考>	0.6	0.51	0.39	0.32	0.50	0.39	0.32	0.27	0.37	0.31	0.26	0.36	0.30	0.26	
	0.8	0.59	0.48	0.41	0.58	0.47	0.40	0.35	0.46	0.39	0.34	0.44	0.38	0.34	
姿図	1	0.65	0.55	0.47	0.63	0.53	0.46	0.41	0.51	0.45	0.40	0.49	0.44	0.39	
	1.25	0.70	0.61	0.53	0.69	0.59	0.53	0.47	0.57	0.51	0.46	0.55	0.50	0.45	
	1.5	0.74	0.65	0.58	0.72	0.64	0.58	0.52	0.62	0.56	0.51	0.59	0.54	0.50	
	2	0.80	0.72	0.66	0.78	0.71	0.65	0.60	0.68	0.63	0.58	0.65	0.61	0.57	
	2.5	0.83	0.76	0.70	0.81	0.75	0.69	0.65	0.72	0.67	0.63	0.69	0.65	0.62	
	3	0.85	0.79	0.74	0.83	0.78	0.73	0.68	0.75	0.70	0.67	0.72	0.68	0.65	
光源	4	0.88	0.83	0.79	0.86	0.82	0.77	0.74	0.79	0.75	0.72	0.76	0.73	0.70	
品名	直管形LEDランプ	5	0.90	0.86	0.82	0.88	0.84	0.81	0.78	0.81	0.78	0.76	0.78	0.76	0.74
形式	LDK40SS-N/22/36NE	7	0.93	0.90	0.87	0.91	0.88	0.85	0.83	0.85	0.83	0.80	0.82	0.80	0.78
光束	3,600 lm	10	0.95	0.93	0.90	0.93	0.91	0.89	0.87	0.88	0.86	0.85	0.85	0.83	0.82
器具効率 Ft=	92.6%														
上方光束 Fu=	4.6%														
下方光束 Fd=	88.0%														
最大取付間隔															
A-A	1.32	H													
B-B	1.24	H													
保守率	良	0.86													
	中	0.81													
	否	0.72													
光度(cd/1000 lm)															
	A-0	B-B	C-0	A'-0	C'-0										
0	266	266	266												
10	264	262	263												
20	253	245	251												
30	232	221	226												
40	211	187	200												
50	184	147	166												
60	155	108	132												
70	128	65	101												
80	102	21	74												
90	80		54												
100	51		18												
110															
120															
130															
140															
150															
160															
170															
180															