

## 日立照明器具 照明特性

形式: NLE32401WW-JZU14 <高出力タイプ> <温白色相当> <照度補正、連続調光共用形>	反射率	天井	80%			70%			50%			30%			0%				
	壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%				
	床	10%												0%					
	室指数	照明率 S/H=1.0																	
姿図	0.6	0.59	0.48	0.40	0.58	0.47	0.40	0.35	0.46	0.39	0.35	0.45	0.39	0.34	0.33				
	0.8	0.69	0.58	0.50	0.67	0.57	0.50	0.45	0.56	0.49	0.44	0.54	0.49	0.44	0.42				
	1	0.75	0.65	0.58	0.74	0.64	0.57	0.52	0.63	0.56	0.52	0.61	0.56	0.51	0.49				
	1.25	0.81	0.72	0.65	0.79	0.71	0.64	0.59	0.69	0.63	0.59	0.67	0.62	0.58	0.56				
	1.5	0.85	0.77	0.71	0.84	0.76	0.70	0.65	0.74	0.69	0.64	0.72	0.68	0.64	0.62				
	2	0.91	0.84	0.78	0.89	0.83	0.78	0.73	0.81	0.76	0.72	0.79	0.75	0.72	0.69				
	2.5	0.94	0.88	0.83	0.93	0.87	0.82	0.78	0.85	0.81	0.77	0.83	0.80	0.76	0.74				
	3	0.96	0.91	0.87	0.95	0.90	0.86	0.82	0.88	0.84	0.81	0.86	0.83	0.80	0.77				
光源	4	0.99	0.95	0.91	0.98	0.94	0.90	0.87	0.92	0.89	0.86	0.89	0.87	0.85	0.82				
品名	LED	5	1.01	0.98	0.95	1.00	0.96	0.94	0.91	0.94	0.92	0.89	0.92	0.90	0.88	0.85			
形式		7	1.03	1.01	0.99	1.02	1.00	0.98	0.96	0.97	0.96	0.94	0.95	0.94	0.92	0.90			
光束	7,450 lm	10	1.05	1.04	1.02	1.04	1.02	1.01	1.00	1.00	0.99	0.98	0.98	0.97	0.96	0.93			
器具効率 Ft=	100.0%	単体照度分布(初期)																	
上方光束 Fu=	0.0%	800 600 400 200																	
下方光束 Fd=	100.0%	0.0 1.5 3.0																	
配光分類	BZ-	3.0 1.5 0.0 1.5 3.0																	
最大取付間隔	A-A	1.32	H	A B															
	B-B	1.14	H	3.0 1.5 0.0 1.5 3.0															
保守率	良	0.81		配光曲線															
	中	0.77		180 150 120 90 60 30 0 30 60 90 120 150 180															
	否	0.68		400.0 350.0 300.0 250.0 200.0 150.0 100.0 50.0 0.0															
光度 (cd/1000 lm)	A-0	B-B	C-0	A'-0	C'-0	A B C-C'													
0	379	379	379			0.0 1.5 3.0 1.5 0.0 3.0													
10	373	361	367			A B C-C'													
20	358	325	342			0.0 1.5 3.0 1.5 0.0 3.0													
30	336	284	304			A B C-C'													
40	299	226	254			0.0 1.5 3.0 1.5 0.0 3.0													
50	257	171	206			A B C-C'													
60	198	113	143			0.0 1.5 3.0 1.5 0.0 3.0													
70	119	55	79			A B C-C'													
80	49	26	31			0.0 1.5 3.0 1.5 0.0 3.0													
90						A B C-C'													
100						0.0 1.5 3.0 1.5 0.0 3.0													
110						A B C-C'													
120						0.0 1.5 3.0 1.5 0.0 3.0													
130						A B C-C'													
140						0.0 1.5 3.0 1.5 0.0 3.0													
150						A B C-C'													
160						A B C-C'													
170						A B C-C'													
180						A B C-C'													

日立アプライアンス株式会社