

日立照明器具 照明特性																			
名称: 一体形LEDベース (スクエアタイプ)		反射率	天井	80%			70%			50%			30%						
			壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%			
形式: NLE324AW-JZ14A		床				10%						0%							
		室指数	固有照明率 S/H=1.0																
<備考>		0.6	0.59	0.47	0.40	0.58	0.47	0.40	0.35	0.46	0.39	0.35	0.45	0.39	0.34	0.33			
		0.8	0.69	0.58	0.50	0.67	0.57	0.50	0.45	0.56	0.49	0.44	0.54	0.49	0.44	0.42			
姿図		1	0.75	0.65	0.58	0.74	0.64	0.57	0.52	0.63	0.56	0.52	0.61	0.56	0.51	0.49			
		1.25	0.81	0.72	0.65	0.79	0.71	0.64	0.59	0.69	0.63	0.59	0.67	0.62	0.58	0.56			
		1.5	0.85	0.77	0.70	0.84	0.76	0.70	0.65	0.74	0.69	0.64	0.72	0.68	0.64	0.62			
		2	0.91	0.84	0.78	0.89	0.83	0.78	0.73	0.81	0.76	0.72	0.79	0.75	0.72	0.69			
		2.5	0.94	0.88	0.83	0.92	0.87	0.82	0.78	0.85	0.81	0.77	0.83	0.79	0.76	0.74			
		3	0.96	0.91	0.86	0.95	0.90	0.86	0.82	0.88	0.84	0.81	0.86	0.83	0.80	0.77			
光源形式		4	0.99	0.95	0.91	0.97	0.94	0.90	0.87	0.91	0.89	0.86	0.89	0.87	0.85	0.82			
		-	5	1.01	0.97	0.94	0.99	0.96	0.93	0.91	0.94	0.92	0.89	0.92	0.90	0.88	0.85		
器具光束		7	1.03	1.01	0.98	1.02	1.00	0.98	0.96	0.97	0.96	0.94	0.95	0.94	0.92	0.90			
		6,060 lm	10	1.05	1.03	1.02	1.04	1.02	1.01	0.99	1.00	0.99	0.98	0.98	0.97	0.96	0.93		
器具効率 Ft= 100%																			
上方光束 Fu= 0%																			
下方光束 Fd= 100%																			
最大取付間隔																			
A-A 1.32 H																			
B-B 1.14 H																			
保守率	良	0.86																	
	中	0.81																	
	否	0.72																	
光度(cd/1000 lm)		A-0	B-B	C-0	A'-0	C'-0													
0	379	379	379																
10	373	361	367																
20	358	325	342																
30	336	284	304																
40	299	226	254																
50	257	171	206																
60	198	113	143																
70	119	55	79																
80	49	26	31																
90																			
100																			
110																			
120																			
130																			
140																			
150																			
160																			
170																			
180																			

