


日立照明器具 照明特性

名称:直管形LED搭載器具	反射率	天井	80%			70%				50%			30%			0%																																																																																																																								
		壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%																																																																																																																								
		床	10%														0%																																																																																																																							
形式:NME4205-JM14AEC	室指数	照明率 S/H=1.0																																																																																																																																						
<備考>	0.6	0.51	0.39	0.32	0.49	0.39	0.32	0.27	0.37	0.31	0.26	0.35	0.30	0.26	0.23																																																																																																																									
	0.8	0.60	0.48	0.41	0.58	0.47	0.40	0.35	0.45	0.39	0.34	0.43	0.38	0.33	0.30																																																																																																																									
姿図 	1	0.65	0.55	0.47	0.63	0.53	0.46	0.41	0.51	0.45	0.40	0.49	0.43	0.39	0.36																																																																																																																									
	1.25	0.71	0.61	0.53	0.68	0.59	0.53	0.47	0.57	0.51	0.46	0.54	0.49	0.45	0.41																																																																																																																									
	1.5	0.75	0.66	0.59	0.72	0.64	0.58	0.52	0.61	0.56	0.51	0.58	0.54	0.50	0.46																																																																																																																									
	2	0.80	0.72	0.66	0.78	0.71	0.65	0.60	0.68	0.63	0.58	0.64	0.60	0.57	0.53																																																																																																																									
	2.5	0.83	0.77	0.71	0.81	0.75	0.70	0.65	0.72	0.67	0.63	0.68	0.65	0.61	0.57																																																																																																																									
	3	0.86	0.80	0.74	0.83	0.78	0.73	0.69	0.74	0.70	0.67	0.71	0.68	0.65	0.60																																																																																																																									
	4	0.89	0.84	0.79	0.86	0.82	0.78	0.74	0.78	0.75	0.72	0.75	0.72	0.70	0.65																																																																																																																									
光源	5	0.91	0.87	0.83	0.89	0.85	0.81	0.78	0.81	0.78	0.76	0.78	0.75	0.73	0.69																																																																																																																									
品名:直管形LEDランプ	形式:LDK40SS-D/15/23NE	7	0.93	0.90	0.87	0.91	0.88	0.86	0.83	0.85	0.82	0.80	0.81	0.79	0.78																																																																																																																									
光束:4,660 lm	10	0.95	0.93	0.91	0.93	0.91	0.89	0.87	0.87	0.86	0.84	0.84	0.83	0.81	0.77																																																																																																																									
器具効率 Ft= 93.4%		単体照度分布(初期値) 800 600 400 200 3.0 1.5 0.0 1.5 3.0 0.0 1.5 3.0 水平距離(m) 垂直距離(m) 0-200 200-400 400-600 600-800 800-1000																																																																																																																																						
上方光束 Fu= 7.8%																																																																																																																																								
下方光束 Fd= 85.6%																																																																																																																																								
最大取付間隔		配光曲線 (cd/1000 lm) 180 150 120 90 60 30 0 300.0 250.0 200.0 150.0 100.0 50.0 0.0 0 30 60 90 120 150 180 A B C-C'																																																																																																																																						
A-A 1.32 H																																																																																																																																								
B-B 1.24 H																																																																																																																																								
保守率	良 0.88 中 0.86 否 0.81																																																																																																																																							
光度 (cd/1000 lm)		<table><tr><td></td><td>A-0</td><td>B-B</td><td>C-0</td><td>A'-0</td><td>C'-0</td></tr><tr><td>0</td><td>258</td><td>258</td><td>258</td><td></td><td></td></tr><tr><td>10</td><td>253</td><td>253</td><td>253</td><td></td><td></td></tr><tr><td>20</td><td>243</td><td>238</td><td>240</td><td></td><td></td></tr><tr><td>30</td><td>228</td><td>214</td><td>220</td><td></td><td></td></tr><tr><td>40</td><td>207</td><td>180</td><td>195</td><td></td><td></td></tr><tr><td>50</td><td>183</td><td>146</td><td>164</td><td></td><td></td></tr><tr><td>60</td><td>155</td><td>105</td><td>131</td><td></td><td></td></tr><tr><td>70</td><td>129</td><td>64</td><td>101</td><td></td><td></td></tr><tr><td>80</td><td>103</td><td>22</td><td>76</td><td></td><td></td></tr><tr><td>90</td><td>51</td><td></td><td>34</td><td></td><td></td></tr><tr><td>100</td><td>38</td><td></td><td>23</td><td></td><td></td></tr><tr><td>110</td><td>29</td><td></td><td>16</td><td></td><td></td></tr><tr><td>120</td><td>23</td><td></td><td>12</td><td></td><td></td></tr><tr><td>130</td><td>16</td><td></td><td>8</td><td></td><td></td></tr><tr><td>140</td><td>11</td><td></td><td>6</td><td></td><td></td></tr><tr><td>150</td><td>7</td><td></td><td>2</td><td></td><td></td></tr><tr><td>160</td><td>1</td><td></td><td>1</td><td></td><td></td></tr><tr><td>170</td><td>1</td><td></td><td></td><td></td><td></td></tr><tr><td>180</td><td></td><td></td><td></td><td></td><td></td></tr></table>																A-0	B-B	C-0	A'-0	C'-0	0	258	258	258			10	253	253	253			20	243	238	240			30	228	214	220			40	207	180	195			50	183	146	164			60	155	105	131			70	129	64	101			80	103	22	76			90	51		34			100	38		23			110	29		16			120	23		12			130	16		8			140	11		6			150	7		2			160	1		1			170	1					180					
	A-0																B-B	C-0	A'-0	C'-0																																																																																																																				
0	258																258	258																																																																																																																						
10	253																253	253																																																																																																																						
20	243																238	240																																																																																																																						
30	228																214	220																																																																																																																						
40	207																180	195																																																																																																																						
50	183																146	164																																																																																																																						
60	155																105	131																																																																																																																						
70	129																64	101																																																																																																																						
80	103																22	76																																																																																																																						
90	51																	34																																																																																																																						
100	38																	23																																																																																																																						
110	29																	16																																																																																																																						
120	23																	12																																																																																																																						
130	16																	8																																																																																																																						
140	11		6																																																																																																																																					
150	7		2																																																																																																																																					
160	1		1																																																																																																																																					
170	1																																																																																																																																							
180																																																																																																																																								