

日立照明器具 照明特性

名称: 直管形LED搭載器具	天井	80%			70%				50%			30%			0%		
		壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%	
形式: NME4223-JM14AE	床	10%															0%
		室指数	照明率 S/H=1.0														
<備考>	0.6	0.51	0.40	0.33	0.50	0.39	0.33	0.28	0.38	0.32	0.28	0.37	0.32	0.28	0.26		
	0.8	0.59	0.49	0.42	0.58	0.48	0.41	0.36	0.47	0.41	0.36	0.46	0.40	0.36	0.34		
姿図	1	0.65	0.55	0.48	0.64	0.54	0.48	0.42	0.53	0.47	0.42	0.52	0.46	0.42	0.40		
	1.25	0.71	0.61	0.55	0.69	0.61	0.54	0.49	0.59	0.53	0.49	0.57	0.52	0.48	0.46		
	1.5	0.75	0.66	0.60	0.73	0.65	0.59	0.54	0.64	0.58	0.54	0.62	0.57	0.53	0.51		
	2	0.80	0.73	0.67	0.78	0.72	0.67	0.62	0.70	0.65	0.62	0.68	0.64	0.61	0.59		
	2.5	0.83	0.77	0.72	0.82	0.76	0.71	0.67	0.74	0.70	0.66	0.72	0.69	0.66	0.63		
	3	0.85	0.80	0.75	0.84	0.79	0.75	0.71	0.77	0.73	0.70	0.75	0.72	0.69	0.67		
光源	4	0.88	0.84	0.80	0.87	0.83	0.79	0.76	0.81	0.78	0.75	0.79	0.76	0.74	0.72		
品名 直管形LEDランプ	5	0.90	0.87	0.83	0.89	0.86	0.83	0.80	0.83	0.81	0.79	0.81	0.79	0.77	0.75		
形式 LDK40SS-D/17/26NE	7	0.92	0.90	0.88	0.91	0.89	0.87	0.85	0.87	0.85	0.83	0.85	0.83	0.82	0.79		
光束 5,240 lm	10	0.94	0.92	0.91	0.93	0.91	0.90	0.88	0.89	0.88	0.87	0.87	0.86	0.85	0.83		

器具効率 Ft= 90.0%					
上方光束 Fu= 0.0%					
下方光束 Fd= 90.0%					
最大取付間隔					
A-A		1.32 H			
B-B		1.24 H			
保守率	良	0.86			
	中	0.81			
	否	0.72			
光度 (cd/1000 lm)					
	A-0	B-B	C-0	A'-0	C'-0
0	288	288	288		
10	283	284	283		
20	270	266	267		
30	251	239	244		
40	228	208	215		
50	200	165	181		
60	169	122	147		
70	129	79	109		
80	50	29	59		
90					
100					
110					
120					
130					
140					
150					
160					
170					
180					

単体照度分布(初期値)

3.0 1.5 0.0 1.5 3.0

0.0 1.5 3.0

A← 水平距離(m) →B

(E)lx

- 0-200
- 200-400
- 400-600
- 600-800
- 800-1000

配光曲線 (cd/1000 lm)

180 150 120 90 60 30 0

300.0 250.0 200.0 150.0 100.0 50.0 0.0

A B C-C'