

日立照明器具 照明特性

名称: 交換形LEDトワ7形	天井 反射率 壁 床	80%			70%				50%			30%			0%		
		70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%		
		10%													0%		
形式: PC4A	室指数	固有照明率 S/H=1.0															
<備考>	0.6	0.57	0.45	0.37	0.55	0.44	0.36	0.31	0.42	0.36	0.31	0.41	0.35	0.30	0.28		
	0.8	0.66	0.54	0.46	0.64	0.53	0.46	0.40	0.51	0.45	0.40	0.50	0.44	0.39	0.37		
 姿図	1	0.72	0.61	0.53	0.70	0.60	0.53	0.47	0.58	0.51	0.46	0.56	0.50	0.46	0.43		
	1.25	0.78	0.68	0.60	0.76	0.67	0.60	0.54	0.64	0.58	0.53	0.62	0.56	0.52	0.49		
	1.5	0.82	0.73	0.66	0.80	0.72	0.65	0.60	0.69	0.63	0.59	0.67	0.62	0.57	0.54		
	2	0.88	0.80	0.74	0.86	0.79	0.73	0.68	0.76	0.71	0.66	0.73	0.69	0.65	0.62		
	2.5	0.91	0.85	0.79	0.89	0.83	0.78	0.73	0.80	0.75	0.71	0.77	0.73	0.70	0.66		
	3	0.94	0.88	0.82	0.91	0.86	0.81	0.77	0.83	0.79	0.75	0.80	0.76	0.73	0.70		
光源形式	4	0.97	0.92	0.88	0.95	0.90	0.86	0.83	0.87	0.84	0.80	0.84	0.81	0.78	0.74		
CE405NB-J14	5	0.99	0.95	0.91	0.97	0.93	0.90	0.87	0.90	0.87	0.84	0.87	0.84	0.82	0.78		
器具光束	7	1.01	0.98	0.96	0.99	0.97	0.94	0.92	0.93	0.91	0.89	0.90	0.88	0.87	0.82		
5,500 lm	10	1.03	1.01	0.99	1.01	0.99	0.98	0.96	0.96	0.95	0.93	0.93	0.92	0.90	0.86		
器具効率 Ft= 100%		単体照度分布(初期値) 単位照度分布(初期値) 3.0 1.5 0.0 1.5 3.0 0.0 1.5 3.0 A← 水平距離(m) →B (m) 高さ 0-200 200-400 400-600 600-800 800-1000															
上方光束 Fu= 5.3%																	
下方光束 Fd= 94.7%																	
最大取付間隔		配光曲線 配光曲線 (cd/1000 lm) 180 150 120 90 60 30 0 350.0 300.0 250.0 200.0 150.0 100.0 50.0 0.0 A B C-C'															
A-A 1.28 H																	
B-B 1.24 H																	
保守率	良																0.88
	中																0.86
否		0.81															
光度 (cd/1000 lm)		A-0	B-B	C-0	A'-0	C'-0	単位照度分布(初期値)										
0	319	319	319														
10	313	313	313														
20	296	292	294														
30	270	262	265														
40	238	222	230														
50	195	172	184														
60	155	128	143														
70	116	77	98														
80	77	28	57														
90	48	1	29														
100	28	1	14														
110	17	1	9														
120	12	1	7														
130	10	1	6														
140	6	1	3														
150	3	1	1														
160	3	1	1														
170	2	1	1														
180																	