

日立照明器具 照明特性

名称: 交換形LED笠付形	天井	80%			70%				50%			30%			0%				
		壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%			
			床	10%														0%	
形式: PC4BCP	反射率	固有照明率 S/H=1.0																	
<備考> キャビースイッチ付	室指数	0.6	0.58	0.46	0.38	0.57	0.45	0.38	0.33	0.44	0.37	0.33	0.43	0.37	0.32	0.31			
		0.8	0.68	0.56	0.48	0.66	0.56	0.48	0.43	0.54	0.47	0.42	0.53	0.47	0.42	0.40			
姿図		1	0.74	0.63	0.56	0.73	0.63	0.55	0.50	0.61	0.55	0.50	0.60	0.54	0.49	0.47			
		1.25	0.80	0.70	0.63	0.79	0.70	0.63	0.57	0.68	0.62	0.57	0.66	0.61	0.56	0.54			
		1.5	0.85	0.76	0.69	0.83	0.75	0.69	0.63	0.73	0.67	0.63	0.71	0.66	0.62	0.60			
		2	0.90	0.83	0.77	0.89	0.82	0.77	0.72	0.80	0.75	0.71	0.78	0.74	0.70	0.68			
		2.5	0.94	0.87	0.82	0.92	0.86	0.81	0.77	0.84	0.80	0.76	0.82	0.79	0.75	0.73			
		3	0.96	0.91	0.86	0.94	0.89	0.85	0.81	0.87	0.83	0.80	0.85	0.82	0.79	0.76			
		4	0.99	0.95	0.91	0.98	0.94	0.90	0.87	0.91	0.88	0.85	0.89	0.87	0.84	0.81			
光源形式	5	1.01	0.97	0.94	1.00	0.96	0.93	0.91	0.94	0.91	0.89	0.92	0.90	0.88	0.85				
器具光束	7	1.03	1.01	0.98	1.02	1.00	0.97	0.95	0.97	0.96	0.94	0.95	0.94	0.92	0.89				
7,060 lm	10	1.05	1.04	1.02	1.04	1.02	1.01	0.99	1.00	0.99	0.98	0.98	0.97	0.96	0.93				
器具効率 Ft= 100%		単体照度分布(初期値)																	
上方光束 Fu= 0%																			
下方光束 Fd= 100%																			
最大取付間隔																			
A-A 1.30 H																			
B-B 1.28 H																			
保守率	良	0.88																	
	中	0.86																	
	否	0.81																	
光度 (cd/1000 lm)		配光曲線 (cd/1000 lm)																	
	A-0															B-B	C-0	A'-0	C'-0
0	338															338	338		
10	332															333	333		
20	317															316	317		
30	293															292	292		
40	258															254	257		
50	216															211	213		
60	160															156	159		
70	103															95	99		
80	33															37	39		
90																2	1		
100																			
110																			
120																			
130																			
140																			
150																			
160																			
170																			
180																			