

日立照明器具 照明特性

名称: 交換形LED笠付形	天井	80%			70%				50%			30%			0%																																																																																																																								
		壁	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%																																																																																																																								
																床	10%													0%																																																																																																									
形式: PC4BCP	反射率	固有照明率 S/H=1.0																																																																																																																																					
<備考> キャパシタ付	室指数	固有照明率 S/H=1.0																																																																																																																																					
	0.6	0.58	0.47	0.39	0.57	0.46	0.39	0.34	0.45	0.38	0.33	0.44	0.38	0.33	0.31																																																																																																																								
姿図	0.8	0.68	0.57	0.49	0.67	0.56	0.49	0.43	0.55	0.48	0.43	0.53	0.47	0.43	0.41																																																																																																																								
	1	0.74	0.64	0.56	0.73	0.63	0.56	0.50	0.61	0.55	0.50	0.60	0.54	0.50	0.48																																																																																																																								
	1.25	0.80	0.71	0.64	0.79	0.70	0.63	0.58	0.68	0.62	0.57	0.66	0.61	0.57	0.55																																																																																																																								
	1.5	0.85	0.76	0.69	0.83	0.75	0.69	0.64	0.73	0.68	0.63	0.71	0.67	0.63	0.60																																																																																																																								
	2	0.90	0.83	0.77	0.89	0.82	0.77	0.72	0.80	0.75	0.71	0.78	0.74	0.71	0.68																																																																																																																								
	2.5	0.94	0.88	0.82	0.92	0.86	0.82	0.77	0.84	0.80	0.77	0.82	0.79	0.76	0.73																																																																																																																								
	3	0.96	0.91	0.86	0.94	0.89	0.85	0.81	0.87	0.83	0.80	0.85	0.82	0.79	0.77																																																																																																																								
光源形式	4	0.99	0.95	0.91	0.97	0.93	0.90	0.87	0.91	0.88	0.85	0.89	0.87	0.84	0.81																																																																																																																								
CE407NB-JX14	5	1.01	0.97	0.94	0.99	0.96	0.93	0.90	0.94	0.91	0.89	0.92	0.90	0.88	0.85																																																																																																																								
器具光束	7	1.03	1.01	0.98	1.02	1.00	0.97	0.95	0.97	0.95	0.94	0.95	0.94	0.92	0.89																																																																																																																								
7,060 lm	10	1.05	1.03	1.02	1.04	1.02	1.01	0.99	1.00	0.99	0.97	0.98	0.97	0.96	0.93																																																																																																																								
器具効率 Ft= 100%		単体照度分布 (初期値)																																																																																																																																					
上方光束 Fu= 0%																																																																																																																																							
下方光束 Fd= 100%																																																																																																																																							
最大取付間隔		配光曲線 (cd/1000 lm)																																																																																																																																					
A-A 1.26 H																																																																																																																																							
B-B 1.24 H																																																																																																																																							
保守率																																																																																																																																							
良	0.88	<table><tr><th>光度 (cd/1000 lm)</th><th>A-0</th><th>B-B</th><th>C-0</th><th>A'-0</th><th>C'-0</th></tr><tr><td>0</td><td>355</td><td>355</td><td>355</td><td></td><td></td></tr><tr><td>10</td><td>348</td><td>348</td><td>348</td><td></td><td></td></tr><tr><td>20</td><td>330</td><td>327</td><td>328</td><td></td><td></td></tr><tr><td>30</td><td>300</td><td>293</td><td>296</td><td></td><td></td></tr><tr><td>40</td><td>261</td><td>250</td><td>256</td><td></td><td></td></tr><tr><td>50</td><td>213</td><td>201</td><td>205</td><td></td><td></td></tr><tr><td>60</td><td>162</td><td>143</td><td>157</td><td></td><td></td></tr><tr><td>70</td><td>105</td><td>90</td><td>98</td><td></td><td></td></tr><tr><td>80</td><td>30</td><td>32</td><td>40</td><td></td><td></td></tr><tr><td>90</td><td></td><td>2</td><td>2</td><td></td><td></td></tr><tr><td>100</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>110</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>120</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>130</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>140</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>150</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>160</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>170</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>180</td><td></td><td></td><td></td><td></td><td></td></tr></table>														光度 (cd/1000 lm)	A-0	B-B	C-0	A'-0	C'-0	0	355	355	355			10	348	348	348			20	330	327	328			30	300	293	296			40	261	250	256			50	213	201	205			60	162	143	157			70	105	90	98			80	30	32	40			90		2	2			100						110						120						130						140						150						160						170						180					
光度 (cd/1000 lm)	A-0															B-B	C-0	A'-0	C'-0																																																																																																																				
0	355															355	355																																																																																																																						
10	348															348	348																																																																																																																						
20	330	327	328																																																																																																																																				
30	300	293	296																																																																																																																																				
40	261	250	256																																																																																																																																				
50	213	201	205																																																																																																																																				
60	162	143	157																																																																																																																																				
70	105	90	98																																																																																																																																				
80	30	32	40																																																																																																																																				
90		2	2																																																																																																																																				
100																																																																																																																																							
110																																																																																																																																							
120																																																																																																																																							
130																																																																																																																																							
140																																																																																																																																							
150																																																																																																																																							
160																																																																																																																																							
170																																																																																																																																							
180																																																																																																																																							
中	0.86																																																																																																																																						
否	0.81																																																																																																																																						