

日立照明器具 照明特性

名称: 直管形LED搭載器具	反射率	天井	80%			70%			50%			30%			0%					
		壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%				
		床	10%												0%					
形式: PKE11208-JL24AF		室指数 照明率 S/H=1.0																		
<備考>		0.6	0.51	0.40	0.32	0.50	0.39	0.32	0.26	0.37	0.31	0.26	0.36	0.30	0.26	0.24				
		0.8	0.60	0.49	0.41	0.58	0.48	0.40	0.35	0.46	0.39	0.34	0.44	0.38	0.34	0.31				
姿図		1	0.66	0.55	0.47	0.64	0.54	0.46	0.41	0.52	0.45	0.40	0.50	0.44	0.40	0.37				
		1.25	0.71	0.61	0.54	0.70	0.60	0.53	0.47	0.58	0.52	0.46	0.56	0.50	0.46	0.43				
		1.5	0.76	0.66	0.59	0.74	0.65	0.58	0.53	0.63	0.57	0.52	0.60	0.55	0.51	0.48				
		2	0.81	0.73	0.67	0.79	0.72	0.66	0.61	0.69	0.64	0.59	0.67	0.62	0.58	0.55				
		2.5	0.85	0.78	0.72	0.83	0.76	0.71	0.66	0.73	0.69	0.64	0.71	0.67	0.63	0.60				
		3	0.87	0.81	0.75	0.85	0.79	0.74	0.70	0.76	0.72	0.68	0.74	0.70	0.67	0.63				
光源		4	0.90	0.85	0.80	0.88	0.83	0.79	0.75	0.81	0.77	0.74	0.78	0.75	0.72	0.68				
品名	直管形LEDランプ	5	0.92	0.88	0.84	0.90	0.86	0.83	0.79	0.83	0.80	0.78	0.81	0.78	0.76	0.72				
形式	LDK110SS-N/34/45F	7	0.95	0.92	0.89	0.93	0.90	0.87	0.85	0.87	0.85	0.83	0.84	0.82	0.80	0.77				
光束	9,000 lm	10	0.97	0.95	0.92	0.95	0.93	0.91	0.89	0.90	0.88	0.87	0.87	0.86	0.85	0.81				
器具効率 $F_t = 94.4\%$		単体照度分布(初期値)																		
上方光束 $F_u = 3.6\%$																				
下方光束 $F_d = 90.8\%$																				
最大取付間隔																				
A-A 1.34 H																				
B-B 1.26 H																				
保守率	良	0.86																		
	中	0.81																		
	否	0.72																		
光度(cd/1000 lm)																				
	A-0	B-B	C-0	A'-0	C'-0															
0	260	260	260																	
10	256	255	255																	
20	247	242	243																	
30	232	219	226																	
40	212	193	202																	
50	190	158	174																	
60	164	121	144																	
70	137	72	114																	
80	105	33	83																	
90	58		39																	
100	34		14																	
110	10																			
120																				
130																				
140																				
150																				
160																				
170																				
180																				