

日立照明器具 照明特性

形式: PM2115S-G	天井	80%			70%				50%			30%			0%
	壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%
	床	10%													0%
	室指数	照明率 S/H=1.0													
姿図 	0.6	0.47	0.35	0.27	0.44	0.33	0.26	0.21	0.30	0.24	0.19	0.26	0.21	0.17	0.13
	0.8	0.55	0.44	0.35	0.52	0.41	0.34	0.28	0.37	0.30	0.26	0.32	0.27	0.23	0.18
	1	0.61	0.50	0.42	0.57	0.47	0.40	0.34	0.42	0.36	0.31	0.37	0.32	0.28	0.22
	1.25	0.67	0.56	0.48	0.62	0.53	0.46	0.40	0.47	0.41	0.36	0.42	0.37	0.33	0.26
	1.5	0.71	0.61	0.53	0.66	0.58	0.51	0.45	0.51	0.46	0.41	0.45	0.41	0.37	0.29
	2	0.76	0.68	0.61	0.72	0.64	0.58	0.52	0.57	0.52	0.48	0.51	0.46	0.43	0.35
	2.5	0.80	0.72	0.66	0.75	0.68	0.62	0.58	0.61	0.56	0.52	0.54	0.50	0.47	0.38
	3	0.82	0.75	0.69	0.77	0.71	0.66	0.61	0.64	0.59	0.56	0.57	0.53	0.50	0.41
	4	0.85	0.80	0.75	0.81	0.76	0.71	0.67	0.68	0.64	0.61	0.60	0.57	0.55	0.45
	5	0.88	0.83	0.78	0.83	0.79	0.75	0.71	0.70	0.67	0.64	0.63	0.60	0.58	0.48
光源		7	0.90	0.87	0.83	0.86	0.82	0.79	0.76	0.74	0.71	0.69	0.66	0.64	0.52
品名	蛍光ランプ	10	0.92	0.90	0.87	0.88	0.85	0.83	0.81	0.77	0.75	0.73	0.69	0.67	0.55
形式	FL20SSW/18														
光束	1,230 lm														

器具効率 Ft= 96.6%
 上方光束 Fu= 31.9%
 下方光束 Fd= 64.8%

配光分類
BZ-

最大取付間隔
 A-A 1.68 H
 B-B 1.22 H

保守率
 良 0.74
 中 0.70
 否 0.62

光度 (cd/1000 lm)			
	A-0	B-B	C-0
0	138	138	138
10	139	133	135
20	143	126	134
30	148	113	131
40	153	95	127
50	152	76	122
60	148	51	111
70	138	28	97
80	128	10	81
90	118		73
100	121		71
110	120		77
120	116		80
130	88		63
140	53		40
150	15		9
160	10		6
170	5		3
180			

単体照度分布(初期)

