

## 日立照明器具 照明特性

名称: 直管形LED搭載器具	反射率	天井	80%			70%			50%			30%			0%
		壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%
形式: PME4105-JM14AE	床	10%													
室指数	照明率 S/H=1.0														
<備考>	0.6	0.51	0.39	0.32	0.49	0.38	0.31	0.26	0.36	0.30	0.25	0.34	0.29	0.25	0.22
	0.8	0.59	0.48	0.40	0.57	0.47	0.39	0.34	0.44	0.38	0.33	0.42	0.36	0.32	0.29
姿図  	1	0.65	0.54	0.46	0.63	0.53	0.46	0.40	0.50	0.44	0.39	0.47	0.42	0.37	0.34
	1.25	0.70	0.60	0.53	0.68	0.59	0.52	0.46	0.55	0.49	0.45	0.52	0.47	0.43	0.39
	1.5	0.74	0.65	0.58	0.72	0.63	0.57	0.52	0.60	0.54	0.50	0.57	0.52	0.48	0.44
	2	0.80	0.72	0.65	0.77	0.70	0.64	0.59	0.66	0.61	0.57	0.62	0.59	0.55	0.50
	2.5	0.83	0.76	0.70	0.80	0.74	0.69	0.64	0.70	0.65	0.61	0.66	0.62	0.59	0.54
	3	0.85	0.79	0.74	0.82	0.77	0.72	0.68	0.73	0.69	0.65	0.69	0.65	0.62	0.57
光源	4	0.88	0.83	0.79	0.86	0.81	0.77	0.73	0.77	0.73	0.70	0.73	0.70	0.67	0.62
品名 直管形LEDランプ	5	0.90	0.86	0.82	0.88	0.84	0.80	0.77	0.79	0.76	0.74	0.75	0.73	0.71	0.65
形式 LDK40SS-D/22/34NE	7	0.93	0.90	0.87	0.90	0.87	0.85	0.82	0.83	0.81	0.78	0.79	0.77	0.75	0.70
光束 3,490 lm	10	0.95	0.93	0.90	0.92	0.90	0.88	0.86	0.86	0.84	0.83	0.82	0.80	0.79	0.73

器具効率 Ft= 94.0%  
 上方光束 Fu= 11.4%  
 下方光束 Fd= 82.6%

最大取付間隔		
A-A	1.32	H
B-B	1.24	H
保守率	良	0.88
	中	0.86
	否	0.81

光度 (cd/1000 lm)					
	A-0	B-B	C-0	A'-0	C'-0
0	247	247	247		
10	242	242	242		
20	232	226	229		
30	216	202	209		
40	197	173	184		
50	173	136	155		
60	152	97	126		
70	125	58	99		
80	100	20	73		
90	79		53		
100	61		37		
110	45		25		
120	34		17		
130	24		12		
140	15		2		
150	2				
160	1				
170					
180					

