



日立照明器具 照明特性

名称: 直管形LED搭載器具	反射率	天井	80%			70%			50%			30%			0%					
		壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%				
		床	10%												0%					
形式: PME4105-JM14AE		室指数 照明率 S/H=1.0																		
<備考>		0.6	0.51	0.39	0.32	0.49	0.38	0.31	0.26	0.36	0.30	0.25	0.34	0.29	0.25	0.22				
		0.8	0.59	0.48	0.40	0.57	0.47	0.39	0.34	0.44	0.38	0.33	0.42	0.36	0.32	0.29				
姿図		1	0.65	0.54	0.46	0.63	0.53	0.46	0.40	0.50	0.44	0.39	0.47	0.42	0.37	0.34				
		1.25	0.70	0.60	0.53	0.68	0.59	0.52	0.46	0.55	0.49	0.45	0.52	0.47	0.43	0.39				
		1.5	0.74	0.65	0.58	0.72	0.63	0.57	0.52	0.60	0.54	0.50	0.57	0.52	0.48	0.44				
		2	0.80	0.72	0.65	0.77	0.70	0.64	0.59	0.66	0.61	0.57	0.62	0.58	0.55	0.50				
		2.5	0.83	0.76	0.70	0.80	0.74	0.69	0.64	0.70	0.65	0.61	0.66	0.62	0.59	0.54				
		3	0.85	0.79	0.74	0.82	0.77	0.72	0.68	0.73	0.69	0.65	0.69	0.65	0.62	0.57				
光源		4	0.88	0.83	0.79	0.86	0.81	0.77	0.73	0.77	0.73	0.70	0.73	0.70	0.67	0.62				
品名	直管形LEDランプ	5	0.90	0.86	0.82	0.88	0.84	0.80	0.77	0.79	0.76	0.74	0.75	0.73	0.71	0.65				
形式	LDK40SS-N/17/27NE	7	0.93	0.90	0.87	0.90	0.87	0.85	0.82	0.83	0.81	0.78	0.79	0.77	0.75	0.70				
光束	2,700 lm	10	0.95	0.93	0.90	0.92	0.90	0.88	0.86	0.86	0.84	0.83	0.82	0.80	0.79	0.73				
器具効率 Ft= 94.0%		単体照度分布(初期値)																		
上方光束 Fu= 11.4%																				
下方光束 Fd= 82.6%																				
最大取付間隔																				
A-A 1.32 H																				
B-B 1.24 H																				
保守率	良	0.88																		
	中	0.86																		
	否	0.81																		
光度(cd/1000 lm)																				
	A-0	B-B	C-0	A'-0	C'-0															
0	247	247	247																	
10	242	242	242																	
20	232	226	229																	
30	216	202	209																	
40	197	173	184																	
50	173	136	155																	
60	152	97	126																	
70	125	58	99																	
80	100	20	73																	
90	79		53																	
100	61		37																	
110	45		25																	
120	34		17																	
130	24		12																	
140	15		2																	
150	2																			
160	1																			
170																				
180																				

