

日立照明器具 照明特性

名称: (アームタイプ)	反射率	天井	80%			70%			50%			30%			0%		
		壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%	
		床	10%												0%		
形式: RBME1101MNC		室指数	固有照明率 S/H=1.0														
<備考>		0.6	0.62	0.50	0.43	0.61	0.50	0.43	0.38	0.49	0.43	0.38	0.48	0.42	0.38	0.36	
		0.8	0.72	0.62	0.55	0.71	0.61	0.55	0.50	0.60	0.54	0.49	0.59	0.53	0.49	0.47	
姿図	1	0.79	0.69	0.63	0.77	0.69	0.62	0.58	0.67	0.62	0.57	0.66	0.61	0.57	0.55		
	1.25	0.85	0.76	0.70	0.83	0.75	0.70	0.65	0.74	0.69	0.65	0.72	0.68	0.64	0.62		
	1.5	0.89	0.82	0.76	0.87	0.81	0.75	0.71	0.79	0.74	0.70	0.77	0.73	0.70	0.68		
	2	0.94	0.88	0.83	0.93	0.87	0.83	0.79	0.85	0.81	0.78	0.84	0.80	0.77	0.75		
	2.5	0.97	0.92	0.88	0.95	0.91	0.87	0.84	0.89	0.86	0.83	0.87	0.84	0.82	0.79		
	3	0.99	0.94	0.91	0.97	0.93	0.90	0.87	0.91	0.88	0.86	0.89	0.87	0.85	0.82		
光源形式		4	1.01	0.98	0.95	1.00	0.97	0.94	0.91	0.95	0.92	0.90	0.93	0.91	0.89	0.86	
-		5	1.03	1.00	0.98	1.02	0.99	0.97	0.95	0.97	0.95	0.93	0.95	0.93	0.92	0.89	
器具光束		7	1.05	1.03	1.01	1.04	1.02	1.00	0.99	1.00	0.98	0.97	0.98	0.97	0.96	0.93	
10,800 lm		10	1.07	1.05	1.04	1.05	1.04	1.03	1.02	1.02	1.01	1.00	1.00	0.99	0.99	0.96	
器具効率 Ft= 100%		単体照度分布(初期値)															
上方光束 Fu= 0%		800 600 400 200															
下方光束 Fd= 100%		0.0 2.5 5.0															
最大取付間隔		5.0 2.5 0.0 2.5 5.0															
A-A 1.50 H		A← 水平距離(m) →B															
B-B H		(m)															
保守率	良	0-200															
	中	200-400															
	否	400-600															
光度(cd/1000 lm)		600-800															
	A-0	B-B	C-0	A'-0	C'-0	800-1000											
0	363					0.0 2.5 5.0											
10	363					A← 水平距離(m) →B											
20	374					(m)											
30	366					90											
40	331					180											
50	224					150											
60	123					120											
70	42					90											
80	3					60											
90						30											
100						0											
110						30											
120						60											
130						90											
140						120											
150						150											
160						180											
170						A											
180						B											