

日立照明器具 照明特性

形式: TE45401D-JZ14		天井 壁 床 反射率	80%			70%				50%			30%			0%			
<定格出力タイプ> <昼光色相当> <照度補正、連続調光共用形>			70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%			
			10%														0%		
			照明率 S/H=1.0																
姿図		0.6	0.59	0.48	0.40	0.58	0.47	0.40	0.35	0.46	0.39	0.35	0.45	0.39	0.34	0.33			
		0.8	0.69	0.58	0.51	0.68	0.57	0.50	0.45	0.56	0.50	0.45	0.55	0.49	0.44	0.42			
		1	0.76	0.65	0.58	0.74	0.65	0.58	0.52	0.63	0.57	0.52	0.62	0.56	0.52	0.49			
		1.25	0.82	0.72	0.65	0.80	0.71	0.65	0.60	0.70	0.64	0.59	0.68	0.63	0.59	0.57			
		1.5	0.86	0.78	0.71	0.84	0.77	0.71	0.66	0.75	0.70	0.65	0.73	0.68	0.65	0.62			
		2	0.92	0.85	0.79	0.90	0.84	0.78	0.74	0.82	0.77	0.73	0.80	0.76	0.73	0.70			
		2.5	0.95	0.89	0.84	0.93	0.88	0.83	0.79	0.86	0.82	0.78	0.84	0.80	0.77	0.75			
		3	0.97	0.92	0.87	0.95	0.91	0.87	0.83	0.89	0.85	0.82	0.87	0.84	0.81	0.78			
		光源		4	1.00	0.96	0.92	0.98	0.95	0.91	0.88	0.92	0.90	0.87	0.90	0.88	0.86	0.83	
品名	LED	5	1.02	0.98	0.95	1.00	0.97	0.94	0.92	0.95	0.93	0.90	0.93	0.91	0.89	0.86			
形式		7	1.04	1.02	0.99	1.03	1.01	0.98	0.97	0.98	0.97	0.95	0.96	0.95	0.93	0.91			
光束	8,870 lm	10	1.06	1.04	1.03	1.04	1.03	1.02	1.00	1.01	1.00	0.99	0.99	0.98	0.97	0.94			
器具効率 Ft= 100.0%			単体照度分布(初期)																
上方光束 Fu= 0.0%																			
下方光束 Fd= 100.0%																			
配光分類																			
BZ-																			
最大取付間隔																			
A-A 1.36 H																			
B-B 1.24 H																			
保守率	良	0.81	配光曲線																
	中	0.77																	
	否	0.68																	
光度 (cd/1000 lm)			0-200 200-400 400-600 600-800 800-1000																
	A-0	B-B															C-0	A'-0	C'-0
0	360	360															360		
10	360	355															356		
20	347	333															340		
30	329	296															312		
40	284	250															274		
50	219	187															218		
60	163	141															154		
70	92	79															89		
80	24	23															25		
90																			
100																			
110																			
120																			
130																			
140																			
150																			
160																			
170																			
180																			